



FBX LED High Bay

16,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution, Frosted Acrylic Lens

16,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution, Frosted Acrylic Lens - 125 lm/W

The FBX LED High Bay is a compact and economical luminaire utilizing the latest in LED technology. With several lumen packages and optical distribution patterns available, the FBX offers exceptional lighting in mid to high ceiling applications. Save energy without straining your project budget or sacrificing your light output.

Product data

| General Information Colour Temperature 4000 K CRI 80 Photometric Distribution Type Direct Mounting Suspended | | |
|------------------------------------------------------------------------------------------------------------------|--|--|
| CRI 80 Photometric Distribution Type Direct Mounting Suspended | | |
| Photometric Distribution Type Direct Mounting Suspended | | |
| Mounting Suspended | | |
| | | |
| Operation and Floridan | | |
| Operating and Floatwice! | | |
| Operating and Electrical | | |
| Voltages 120/208/240/277/347/480/UNIV V | | |
| Luminaire Input Watts 124 | | |
| | | |
| Initial Performance (IEC Compliant) | | |
| Luminaire Lumens 16000 | | |
| Efficacy 125 lm/W | | |
| Efficacy 125 lm/W | | |

| Product Data | | |
|-----------------------------------|-------------------------------------------------|--|
| Order product name | FBX16LL40-UNV | |
| EAN/UPC - Product | 781370690229 | |
| Order code | FBX16LL40-UNV-LFA | |
| Numerator - Quantity Per Pack | 1 | |
| Numerator - Packs per outer box 1 | | |
| Material Nr. (12NC) | 912401266171 | |
| Net Weight (Piece) | 0.001 kg | |
| Catalog Number | FBX16LL40-UNV-LFA | |
| Catalog Number Description | 16,000 Nominal Delivered Lumens, 4000K, 80 CRI, | |
| | General Distribution, Frosted Acrylic Lens | |

Datasheet, 2019, July 28 data subject to change