



FBX LED High Bay

16,000 Nominal Delivered Lumens, 4000K, 80 CRI, Medium Distribution, Frosted Acrylic Lens

16,000 Nominal Delivered Lumens, 4000K, 80 CRI, Medium Distribution, Frosted Acrylic Lens - 130 lm/W

The FBX LED High Bay is a compact and economical luminaire utilizing the latest in LED technology. With several lumen packages and optical distribution patterns available, the FBX offers exceptional lighting in mid to high ceiling applications. Save energy without straining your project budget or sacrificing your light output.

Product data

General Information	
Colour Temperature	4000 K
CRI	80
Photometric Distribution Type	Direct
Mounting	Suspended
Operating and Electrical	
Voltages	120/208/240/277/347/480/UNIV V
Luminaire Input Watts	124
Initial Performance (IEC Compliant)	
Luminaire Lumens	16000
Efficacy	130 lm/W

Product Data	
Order product name	FBX16LL40-UNV
EAN/UPC - Product	781370387938
Order code	FBX16LL40-UNV-M-LFA
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912401267298
Net Weight (Piece)	0.001 kg
Catalog Number	FBX16LL40-UNV-M-LFA
Catalog Number Description	16,000 Nominal Delivered Lumens, 4000K, 80 CRI, Medium Distribution, Frosted Acrylic Lens