



FBX LED High Bay

20,000 Nominal Delivered Lumens, 4000K, 80 CRI, Aisle Distribution, Prismatic Acrylic Lens

20,000 Nominal Delivered Lumens, 4000K, 80 CRI, Aisle Distribution, Prismatic Acrylic Lens - 137 lm/W

The FBX LED High Bay is a compact and economical luminaire utilizing the latest in LED technology. With several lumen packages and optical distribution patterns available, the FBX offers exceptional lighting in mid to high ceiling applications. Save energy without straining your project budget or sacrificing your light output.

Product data

General Information	
Colour Temperature	4000 K
CRI	80
Photometric Distribution Type	Direct
Mounting	Suspended
Operating and Electrical	
Voltages	120/208/240/277/347/480/UNIV V
Luminaire Input Watts	142
Initial Performance (IEC Compliant)	
Luminaire Lumens	20000
Efficacy	137 lm/W

FBX20LL40-UNV	
781370407414	
FBX20LL40-UNV-A-LPA	
1	
Numerator - Packs per outer box 1	
912401267354	
0.001 kg	
FBX20LL40-UNV-A-LPA	
20,000 Nominal Delivered Lumens, 4000K, 80 CRI,	
Aisle Distribution, Prismatic Acrylic Lens	