



# SofTrace Surface LED

**2x4, Surface, 4200 Nominal Delivered Lumens, 80 CRI, 3500K, Round Perf. w/White Overlay**

2x4, Surface, 4200 Nominal Delivered Lumens, 80 CRI, 3500K, Round Perf. w/White Overlay

SofTrace Surface LED brings new meaning to the concept of combining style with performance. Equipped with a fresh streamlined design and innovative technology, SofTrace provides a huge step forward for the lighting industry. The sleek profile design belies the true “horsepower under the hood”. With efficiency levels exceeding 95% and lumens per Watt as great as 87, an architectural product now delivers leading edge performance for the most environmentally conscious user.

## Product data

General Information	
Lamp Source Code	LED
Colour Temperature	3500K
CRI	80
Photometric Distribution Type	Direct
Mounting	Surface
Operating and Electrical	
Voltages	120/277/347 V
Luminaire Input Watts	41
Mechanical and Housing	
Fixture Size	2 ft x 4 ft
Shape	Rectangular
Initial Performance (IEC Compliant)	
Luminaire Lumens	4200

Product Data	
Order product name	2SST42L835-4-PMW-UNV
EAN/UPC - Product	784197036539
Order code	2SST42L835-4-PMW-UNV-DIM
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912401270916
Net Weight (Piece)	0.001 kg
Catalog Number	2SST42L835-4-PMW-UNV-DIM
Catalog Number Description	2x4, Surface, 4200 Nominal Delivered Lumens, 80 CRI, 3500K, Round Perf. w/White Overlay

## SofTrace Surface LED

