

FBX LED High Bay

8,000 Nominal Delivered Lumens, 4000K, 80 CRI, Medium Distribution, Frosted Acrylic Lens

8,000 Nominal Delivered Lumens, 4000K, 80 CRI, Medium Distribution, Frosted Acrylic Lens - 135 lm/W

The FBX LED High Bay is a compact and economical luminaire utilizing the latest in LED technology. With several lumen packages and optical distribution patterns available, the FBX offers exceptional lighting in mid to high ceiling applications. Save energy without straining your project budget or sacrificing your light output.

Product data

General Information	
Colour Temperature	4000 K
CRI	80
Photometric Distribution Type	Direct
Mounting	Suspended

Operating and Electrical	
Voltages	120/208/240/277/347/480/UNIV V
Luminaire Input Watts	61

Initial Performance (IEC Compliant)	
Luminaire Lumens	8000
Efficacy	135 lm/W

Product Data	
Order product name	FBX08LL40-UNV
EAN/UPC - Product	784197086183
Order code	FBX08LL40-UNV-M-LFA
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912401274352
Net Weight (Piece)	0.001 kg
Catalog Number	FBX08LL40-UNV-M-LFA
Catalog Number Description	8,000 Nominal Delivered Lumens, 4000K, 80 CRI, Medium Distribution, Frosted Acrylic Lens