



LBX LED Linear Suspended

4', 5,500 Nominal Delivered Lumens, 4000K, 80 CRI, Medium Distribution

4', 5,500 Nominal Delivered Lumens, 4000K, 80 CRI, Medium Distribution - 148 lm/W

The LBX LED linear suspended luminaires with optional LightBalance Optics provide the versatility required for a wide range of applications. Available in 5 different configurations, LBX is easy to install and can be mounted together in runs. Where precise control is required, LightBalance Optics put the light where it's needed. Choose between narrow, medium, wide, aisle, & double asymmetric distributions.

Product data

General Information	
Colour Temperature	4000 K
CRI	80
Photometric Distribution Type	Direct
Mounting	Suspended
Operating and Electrical	
Voltages	347/UNIV V
Luminaire Input Watts	41
Mechanical and Housing	
Fixture Size	48 in
Shape	Linear

Initial Performance (IEC Compliant)	
Luminaire Lumens	5500
Efficacy	148 lm/W
Product Data	
Order product name	LBX55L840-UNV
EAN/UPC - Product	784197183912
Order code	LBX55L840-UNV-M
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912401278441
Net Weight (Piece)	0.001 kg
Catalog Number	LBX55L840-UNV-M

LBX LED Linear Suspended

Catalog Number	Description
	4', 5,500 Nominal Delivered Lumens, 4000K, 80 CRI, Medium Distribution

