



LBX LED Linear Suspended

4', 7,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution, Flat Diffuse Lens

4', 7,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution, Flat Diffuse Lens – 125 lm/W

The LBX LED linear suspended luminaires with optional LightBalance Optics provide the versatility required for a wide range of applications. Available in 5 different configurations, LBX is easy to install and can be mounted together in runs. Where precise control is required, LightBalance Optics put the light where it's needed. Choose between narrow, medium, wide, aisle, & double asymmetric distributions.

Product data

| General Information | | Initial Performance (IEC Compliant) | |
|-------------------------------|------------|-------------------------------------|------------------|
| Colour Temperature | 4000 K | Luminaire Lumens | 7000 |
| CRI | 80 | Efficacy | 125 lm/W |
| Photometric Distribution Type | Direct | | |
| Mounting | Suspended | | |
| Operating and Electrical | | Product Data | |
| Voltages | 347/UNIV V | Order product name | LBX70L840-UNV |
| Luminaire Input Watts | 53 | EAN/UPC - Product | 784197188467 |
| | | Order code | LBX70L840-UNV-FD |
| | | Numerator - Quantity Per Pack | 1 |
| | | Numerator - Packs per outer box | 1 |
| Mechanical and Housing | | Material Nr. (12NC) | 912401278812 |
| Fixture Size | 48 in | Net Weight (Piece) | 0.001 kg |
| Shape | Linear | Catalog Number | LBX70L840-UNV-FD |

LBX LED Linear Suspended

| | |
|----------------|---|
| Catalog Number | Description |
| | 4', 7,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution, Flat Diffuse Lens |

