

Lighting

PHILIPS

LBX LED Linear Suspended

4', 4,000 Nominal Delivered Lumens, 4000K, 80 CRI, Aisle Distribution

4', 4,000 Nominal Delivered Lumens, 4000K, 80 CRI, Aisle Distribution – 151 lm/W

The LBX LED linear suspended luminaires with optional LightBalance Optics provide the versatility required for a wide range of applications. Available in 5 different configurations, LBX is easy to install and can be mounted together in runs. Where precise control is required, LightBalance Optics put the light where it's needed. Choose between narrow, medium, wide, aisle, & double asymmetric distributions.

Product data

General Information		Initial Performance (IEC Co	mpliant)	
Colour Temperature	4000 K	Luminaire Lumens	4000	
CRI	80	Efficacy	151 lm/W	
Photometric Distribution Type	Direct			
Mounting	Suspended	Product Data		
		Order product name	LBX40L840-UNV	
Operating and Electrical		EAN/UPC - Product	784197190996	
Voltages	347/UNIV V	Order code	LBX40L840-UNV-A	
Luminaire Input Watts	31	Numerator - Quantity Per Pack	1	
		Numerator - Packs per outer bo	Numerator - Packs per outer box 1	
Mechanical and Housing		Material Nr. (12NC)	912401279085	
Fixture Size	48 in	Net Weight (Piece)	0.001 kg	
Shape	Linear	Catalog Number	LBX40L840-UNV-A	

LBX LED Linear Suspended

Catalog Number Description 4', 4,000 Nominal Delivered Lumens, 4000K, 80 CRI, Aisle Distribution



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2019, May 6 - data subject to change