



LBX LED Linear Suspended

4', 4,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution, Oval Uplight Diffuse Lens

4', 4,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution, Oval Uplight Diffuse Lens - 137 lm/W

The LBX LED linear suspended luminaires with optional LightBalance Optics provide the versatility required for a wide range of applications. Available in 5 different configurations, LBX is easy to install and can be mounted together in runs. Where precise control is required, LightBalance Optics put the light where it's needed. Choose between narrow, medium, wide, aisle, & double asymmetric distributions.

Product data

General Information		Shape	
Colour Temperature	4000 K	Linear	
CRI	80	Initial Performance (IEC Compliant)	
Photometric Distribution Type	Direct	Luminaire Lumens	4000
Mounting	Suspended	Efficacy	137 lm/W
Operating and Electrical		Product Data	
Voltages	347/UNIV V	Order product name	LBX40L840-UNV
Luminaire Input Watts	31	EAN/UPC - Product	784197335397
Mechanical and Housing		Order code	LBX40L840-UNV-UD
Fixture Size	48 in	Numerator - Quantity Per Pack	1
		Numerator - Packs per outer box	1
		Material Nr. (12NC)	912401279087

LBX LED Linear Suspended

Net Weight (Piece)	0.001 kg
Catalog Number	LBX40L840-UNV-UD
Catalog Number Description	4', 4,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution, Oval Uplight Diffuse Lens

