



LBX LED Linear Suspended

4', 5,500 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution, Oval Uplight Diffuse Lens

4', 5,500 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution, Oval Uplight Diffuse Lens - 135 lm/W

The LBX LED linear suspended luminaires with optional LightBalance Optics provide the versatility required for a wide range of applications. Available in 5 different configurations, LBX is easy to install and can be mounted together in runs. Where precise control is required, LightBalance Optics put the light where it's needed. Choose between narrow, medium, wide, aisle, & double asymmetric distributions.

Product data

General Information		Shape	
Colour Temperature	4000 K	Linear	
CRI	80	Initial Performance (IEC Compliant)	
Photometric Distribution Type	Direct	Luminaire Lumens	5500
Mounting	Suspended	Efficacy	135 lm/W
Operating and Electrical		Product Data	
Voltages	347/UNIV V	Order product name	LBX55L840-UNV
Luminaire Input Watts	41	EAN/UPC - Product	784197191139
Mechanical and Housing		Order code	LBX55L840-UNV-UD
Fixture Size	48 in	Numerator - Quantity Per Pack	1
		Numerator - Packs per outer box	1
		Material Nr. (12NC)	912401279097

LBX LED Linear Suspended

Net Weight (Piece)	0.001 kg
Catalog Number	LBX55L840-UNV-UD
Catalog Number Description	4', 5,500 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution, Oval Uplight Diffuse Lens

