



LBX LED Linear Suspended

4', 7,000 Nominal Delivered Lumens, 4000K, 80 CRI, Medium Distribution

4', 7,000 Nominal Delivered Lumens, 4000K, 80 CRI, Medium Distribution - 145 lm/W

The LBX LED linear suspended luminaires with optional LightBalance Optics provide the versatility required for a wide range of applications. Available in 5 different configurations, LBX is easy to install and can be mounted together in runs. Where precise control is required, LightBalance Optics put the light where it's needed. Choose between narrow, medium, wide, aisle, & double asymmetric distributions.

Product data

| General Information | |
|-------------------------------|------------|
| Colour Temperature | 4000 K |
| CRI | 80 |
| Photometric Distribution Type | Direct |
| Mounting | Suspended |
| Operating and Electrical | |
| Voltages | 347/UNIV V |
| Luminaire Input Watts | 53 |
| Mechanical and Housing | |
| Fixture Size | 48 in |
| Shape | Linear |

| Initial Performance (IEC Compliant) | |
|-------------------------------------|-----------------|
| Luminaire Lumens | 7000 |
| Efficacy | 145 lm/W |
| Product Data | |
| Order product name | LBX70L840-UNV |
| EAN/UPC - Product | 784197191160 |
| Order code | LBX70L840-UNV-M |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 1 |
| Material Nr. (12NC) | 912401279101 |
| Net Weight (Piece) | 0.001 kg |
| Catalog Number | LBX70L840-UNV-M |

LBX LED Linear Suspended

| Catalog Number | Description |
|----------------|---|
| | 4', 7,000 Nominal Delivered Lumens, 4000K, 80 CRI, Medium Distribution |

