



# LBX LED Linear Suspended

4', 7,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution, Oval Uplight Diffuse Lens

4', 7,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution, Oval Uplight Diffuse Lens - 133 lm/W

The LBX LED linear suspended luminaires with optional LightBalance Optics provide the versatility required for a wide range of applications. Available in 5 different configurations, LBX is easy to install and can be mounted together in runs. Where precise control is required, LightBalance Optics put the light where it's needed. Choose between narrow, medium, wide, aisle, & double asymmetric distributions.

## Product data

<b>General Information</b>		<b>Shape</b>	
Colour Temperature	4000 K	Linear	
CRI	80	<b>Initial Performance (IEC Compliant)</b>	
Photometric Distribution Type	Direct	Luminaire Lumens	7000
Mounting	Suspended	Efficacy	133 lm/W
<b>Operating and Electrical</b>		<b>Product Data</b>	
Voltages	347/UNIV V	Order product name	LBX70L840-UNV
Luminaire Input Watts	53	EAN/UPC - Product	784197191290
<b>Mechanical and Housing</b>		Order code	LBX70L840-UNV-UD
Fixture Size	48 in	Numerator - Quantity Per Pack	1
		Numerator - Packs per outer box	1
		Material Nr. (12NC)	912401279112

LBX LED Linear Suspended

Net Weight (Piece)	0.001 kg
Catalog Number	LBX70L840-UNV-UD
Catalog Number Description	4', 7,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution, Oval Uplight Diffuse Lens

