



LBX LED Linear Suspended

8', 11,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution

8', 11,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution – 150 lm/W

The LBX LED linear suspended luminaires with optional LightBalance Optics provide the versatility required for a wide range of applications. Available in 5 different configurations, LBX is easy to install and can be mounted together in runs. Where precise control is required, LightBalance Optics put the light where it's needed. Choose between narrow, medium, wide, aisle, & double asymmetric distributions.

Product data

General Information	
Colour Temperature	4000 K
CRI	80
Photometric Distribution Type	Direct
Mounting	Suspended
Operating and Electrical	
Voltages	347/UNIV V
Luminaire Input Watts	86
Mechanical and Housing	
Fixture Size	96 in
Shape	Linear

Initial Performance (IEC Compliant)	
Luminaire Lumens	11000
Efficacy	150 lm/W
Product Data	
Order product name	LBX110L840-UNV
EAN/UPC - Product	784197192174
Order code	LBX110L840-UNV
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box 1	
Material Nr. (12NC)	912401279187
Net Weight (Piece)	0.001 kg
Catalog Number	LBX110L840-UNV

Datasheet, 2019, May 6 data subject to change

LBX LED Linear Suspended

Catalog Number Description

 $8^{\prime}, 11{,}000$ Nominal Delivered Lumens, 4000K, 80 CRI,

General Distribution



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.