



DuaLED Surface LED

2x2, 2100 Nominal Delivered Lumens, 3500K, Diffuse, Surface Mount

2x2, 2100 Nominal Delivered Lumens, 3500K, Diffuse, Surface Mount - 95 lm/W

Surface DuaLED was thoughtfully developed as a sustainable luminaire with a modern appearance and uncomplicated design, also offering exceptional quality and performance, for an outstanding benefit to the customer. DuaLED is a highly efficient, architecturally styled recessed LED luminaire designed with a minimalistic strategy to achieve sustainable objectives. It combines an extremely low profile with clean aesthetics and is powered by highly efficient advanced LED sources, providing the utmost in comfortable efficient lighting. Driver and integral control options ensure optimization for every application. Designed for excellent visual comfort, DuaLED is perfect for a wide variety of general applications like offices, schools, retail, or healthcare. Optional SpaceWise automated wireless technology provides integrated occupancy and daylight harvesting for additional control and energy savings with no reduction of life.

Product data

General Information	
Lamp Source Code	LED
Colour Temperature	3500K
CRI	80
Photometric Distribution Type	Direct
Mounting	Surface
Operating and Electrical	
Voltages	120/277/347 V

Luminaire Input Watts	22
Mechanical and Housing	
Fixture Size	2 ft x 2 ft
Shape	Square
Initial Performance (IEC Compliant)	
Luminaire Lumens	2100
Efficacy	95 lm/W

DuaLED Surface LED

Product Data

Order product name	2SDL21L835-2-D-UNV
EAN/UPC - Product	784197234126
Order code	2SDL21L835-2-D-UNV-DIM
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912401281583

Net Weight (Piece)	0.001 kg
Catalog Number	2SDL21L835-2-D-UNV-DIM
Catalog Number Description	2x2, 2100 Nominal Delivered Lumens, 3500K, Diffuse, Surface Mount

