

SofTrace Surface LED

2x2, Surface, 3000 Nominal Delivered Lumens, 80 CRI, 4000K, Diffuse-Smooth

2x2, Surface, 3000 Nominal Delivered Lumens, 80 CRI, 4000K, Diffuse-Smooth

SofTrace Surface LED brings new meaning to the concept of combining style with performance. Equipped with a fresh streamlined design and innovative technology, SofTrace provides a huge step forward for the lighting industry. The sleek profile design belies the true “horsepower under the hood”. With efficiency levels exceeding 95% and lumens per Watt as great as 87, an architectural product now delivers leading edge performance for the most environmentally conscious user.

Product data

General Information	
Lamp Source Code	LED
Colour Temperature	4000K
CRI	80
Photometric Distribution Type	Direct
Mounting	Surface

Operating and Electrical	
Voltages	120/277/347 V
Luminaire Input Watts	33

Mechanical and Housing	
Fixture Size	2 ft x 2 ft
Shape	Square

Initial Performance (IEC Compliant)	
Luminaire Lumens	3000

Product Data	
Order product name	2SST30L840-2-DS-UNV
EAN/UPC - Product	784197248161
Order code	2SST30L840-2-DS-UNV-DIM
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912401282437
Net Weight (Piece)	0.001 kg
Catalog Number	2SST30L840-2-DS-UNV-DIM
Catalog Number Description	2x2, Surface, 3000 Nominal Delivered Lumens, 80 CRI, 4000K, Diffuse-Smooth

SofTrace Surface LED



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com
2019, May 6 - data subject to change