



SofTrace Air LED

2x2, Air Handling, 3000 Nominal Delivered Lumens, 80 CRI, 3500K, Diffuse-Smooth

2x2, Air Handling, 3000 Nominal Delivered Lumens, 80 CRI, 3500K, Diffuse-Smooth

SofTrace Air LED brings new meaning to the concept of combining style with performance. Equipped with a fresh streamlined design and innovative technology, SofTrace provides a huge step forward for the lighting industry. The sleek profile design belies the true “horsepower under the hood”. With efficiency levels exceeding 95% and lumens per Watt as great as 87, an architectural product now delivers leading edge performance for the most environmentally conscious user.

Product data

General Information		Product Data	
Lamp Source Code	LED	Order product name	2STGA30L835-2-DS-UNV
Colour Temperature	3500K	EAN/UPC - Product	784197252083
CRI	80	Order code	2STGA30L835-2-DS-UNV-DIM
Photometric Distribution Type	Direct	Numerator - Quantity Per Pack	1
Mounting	Recessed	Numerator - Packs per outer box	1
Operating and Electrical		Material Nr. (12NC)	912401282625
Voltages	120/277/347 V	Net Weight (Piece)	0.001 kg
Luminaire Input Watts	33	Catalog Number	2STGA30L835-2-DS-UNV-DIM
Mechanical and Housing		Catalog Number Description	2x2, Air Handling, 3000 Nominal Delivered Lumens, 80 CRI, 3500K, Diffuse-Smooth
Fixture Size	2 ft x 2 ft		
Initial Performance (IEC Compliant)			
Luminaire Lumens	3000		

