



# SofTrace Air LED

## 2STGA42L835-4-DS-UNV

2x4, Air Handling, 4200 Nominal Delivered Lumens, 80 CRI, 3500K, Diffuse-Smooth

SofTrace Air LED brings new meaning to the concept of combining style with performance. Equipped with a fresh streamlined design and innovative technology, SofTrace provides a huge step forward for the lighting industry. The sleek profile design belies the true “horsepower under the hood”. With efficiency levels exceeding 95% and lumens per Watt as great as 87, an architectural product now delivers leading edge performance for the most environmentally conscious user.

### Product data

General Information	
Lamp Source Code	LED
Color Temperature	3500K
CRI	80
Photometric Distribution Type	Direct
Mounting	Recessed
Operating and Electrical	
Voltages	120/277/347 V
Luminaire Input Watts	41
Mechanical and Housing	
Fixture Size	2 ft x 4 ft
Initial Performance (IEC Compliant)	
Luminaire Lumens	4200

Product Data	
Order product name	2STGA42L835-4-DS-UNV
EAN/UPC - Product	784197095963
Order code	912401287022
Local order code	9709596
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	912401287022
Net Weight (Piece)	0.001 kg
Commercial Code	2STGA42L835-4-DS-UNV-DIM
Catalog Number Description	2x4, Air Handling, 4200 Nominal Delivered Lumens, 80 CRI, 3500K, Diffuse-Smooth
Quick Ship	-