


Gear for SDW-T lamps

CSLS 50 SDW-T 220-240V 50/60HZ

CSLS electronic control unit with impregnated (HID "BASIC") or encapsulated (HID "Heavy Duty") electromagnetic ballasts

Warnings and Safety

- Climatic suitability CSLS and HID BASIC: restricted to built in situations under normal conditions
- Climatic suitability CSLS and HID Heavy Duty: use in luminaires under humid conditions (not drip-proof)

Product data

Operating and Electrical	
Input Voltage	220 to 240 V
Input frequency	50 to 60 Hz

Wiring	
Cable length from device to lamp	0.50 m
Connector type	Screw


Temperature	
T-case lifetime (nom.)	90 °C
T-Case maximum (max.)	90 °C

Approval and Application	
Approval marks	CE marking VDE-EMV certificate CB Certificate

Product Data	
Order product name	CSLS 50 SDW-T 220-240V 50/60Hz
Full product name	CSLS 50 SDW-T 220-240V 50/60HZ
Full EOC	871150090808730
Order code	90808730
Material no. (12 NC)	913619179966
Local order code	CSLS50
SAP numerator – quantity per pack	1
EAN/UPC — Product/Case	8711500908087
Numerator – packs per outer box	18
EAN/UPC - Case	8711500908094

Gear for SDW-T lamps

Dimensional drawing



Product	D1	C1	A1	A2	B1	B2
CSLS 50 SDW-T 220-240V 50/60Hz	4.5 mm	39.5 mm	98.0 mm	70.0 mm	58.5 mm	46.0 mm

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.