



HID ignitors for series systems

SX 72 220-240V 50/60HZ

HID ignitors for series systems

Product data


Operating and Electrical				
Input Voltage	220 to 240 V			
Line Frequency	50 to 60 Hz			
Input frequency	50 to 60 Hz			
Wiring				
Connector type	Screw			
Temperature				
Ambient temperature range	-20°C to 75°C			
T-Case maximum (max.)	80 °C			
Mechanical and Housing				
Housing	SNI-115			
Approval and Application				
Approval marks	CE marking ENEC certificate			

Product Data		
Order product name	SX 72 220-240V 50/60Hz	
Full product name	SX 72 220-240V 50/60HZ	
Full EOC	871150091561030	
Local code description	SX72	
Order code	91561030	
Material no. (12 NC)	913654059066	
Local order code	SX72	
SAP numerator – quantity per pack	1	
EAN/UPC — Product/Case	8711500915610	
Numerator – packs per outer box	20	
EAN/UPC - Case	8711500914361	

Datasheet, 2023, April 30 data subject to change

HID ignitors for series systems

Dimensional drawing



Product	D1	C1	A1	A2	B1
SX 72 220-240V 50/60Hz	4.3 mm	38.0 mm	114.5 mm	95.0 mm	41.0 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.