



HID-HighPower for SON/MH/HPL/HPI

BSN 1000 L78-A2 230/240V 50Hz HP-257

Encapsulated ballasts for use with SON (T) (Plus), HPL, HPI and MH lamps with rated wattages of 1000 W and above

Product data

Operating and Electrical						
Input Voltage	230 V (default) or 240 V					
Line Frequency	50 Hz					
Input Frequency	50 Hz					
Wiring						
Connector Type	Screw					
Approval and Application						
Approval Marks	CE marking ENEC certificate					
Product Data						
<u> </u>	DON 4000 1 70 40 000 (0 40) / FOLL 11D 057					


Full product name	BSN 1000 L78-A2 230/240V 50Hz HP-257
Full product code	871150006236900
Order code	913700217503
Material Nr. (12NC)	913700217503
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500996640
Numerator - Packs per outer box	1
EAN/UPC - Case	8711500062369

Order product name

BSN 1000 L78-A2 230/240V 50Hz HP-257

HID-HighPower for SON/MH/HPL/HPI

Dimensional drawing



Product	D1	C1	A1	A2	A3	B1	B2
BSN 1000 L78-A2	6.5	102.0	257.0	222.0	246.0	117.0	88.0
230/240V 50Hz	mm	mm	mm	mm	mm	mm	mm
HP-257							



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2024, February 7 - data subject to change