



Core & Coil (71A) LPS

CORE & COIL HID LPS BAL 90W L72 QUAD C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information					
ANSI Code	L72				
Lamp Type	90W LPS				
Number of Lamps	1 piece/unit				
Circuit Type	HX-HPF				
Ballast Type	Magnetic HID				
Base Model	71A0590				
Core Size	4 1/4 x 4 3/4 (2 coil)				
Suitable For Outdoor Use	Yes				
Capacitor Value	17.5 MFD				
Capacitor Catalog Number	7C175M30RA				
Capacitor Requirements	300V				
Capacitor Temperature Rating	105°C				
Capacitor Diameter/Oval Dimensions	1.65 in				
Capacitor Height	3.7 in				
Automatic Restart	No				
Operating and Electrical					
Input Voltage	120/208/240/277 V				
Input Frequency	60 Hz				
Input Current (Open Circuit)	4.1/2.3/2/1.75 A				
Input Current (Starting)	1.15/0.65/0.6/0.52 A				
Input Current (Short Circuit)	0.32-0.48/0.17-0.26/0.16-0.24/0.13-0.2 A				
Secondary Short Circuit Current	0.9-1.1 A				

Constant Wattage Deviation	10%	
Ballast Factor (Nom)	1	
Power Factor (Nom)	0.90	
Open Circuit Voltage	515 V	
Input Current (Nom)	1.06/0.6/0.53/0.5 A A	
Input Power (Nom)	125 W	
Rated Lamp Power	90 W	
Wiring		
Wire Striplength	0.5 mm	
Wire Length by Color	12"	
Wire Type	Stranded	
Remote Wiring Configuration Allowed	ed Yes	
Max Ballast-Lamp Distance Remote	Determined by AWG used	
Wiring		
	11/6/5/5 A	
	11/6/5/5 A	
Wiring Recommended Fuse Value Approval and Application	11/6/5/5 A	
Recommended Fuse Value	11/6/5/5 A 460-565 V	
Recommended Fuse Value Approval and Application Open Circuit Voltage Test (Volts)		
Recommended Fuse Value Approval and Application	460-565 V	
Approval and Application Open Circuit Voltage Test (Volts) Approval Marks	460-565 V ULR CSA certificate RoHS Compliant	
Approval and Application Open Circuit Voltage Test (Volts) Approval Marks Temperature Marking	460-565 V ULR CSA certificate RoHS Compliant A/A/A/A	
Approval and Application Open Circuit Voltage Test (Volts) Approval Marks Temperature Marking UL Recognized	460-565 V ULR CSA certificate RoHS Compliant A/A/A/A Yes	


Datasheet, 2019, March 22 data subject to change

Core & Coil (71A) LPS

UL Insulation Class	H(180°C)
UL Temperature Code	1029A
Product Data	
Order product name	CORE & COIL HID LPS BAL 90W L72 QUAD C&C
EAN/UPC - Product	781087120019
Order code	177048

Local order code	177048
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	913700502061
Net Weight (Piece)	4.623 kg

Dimensional drawing



LPS BAL 90W L72 QUAD C&C

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID LPS BAL 90W L72	3.25 in	2.25 in	4.8 in	4.4 in	4.3 in	3.9 in
QUAD C&C						

