



# Core & Coil (71A) HPS ~LT~ 200W

# **CORE & COIL HID HPS BAL 100W S54 QUAD KIT**

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

### **Product data**

General Information				
ANSI Code	S54			
Lamp Type	100W HPS			
Number of Lamps	1 piece/unit			
Circuit Type	HX-HPF			
Ballast Type	Magnetic HID			
Base Model	71A8091			
Core Size	3 X 4 (2 LW)			
Suitable For Outdoor Use	Yes			
Ignitor Catalog Number	LI551-H4			
Ignitor Temperature Rating	105°C			
Capacitor Value	10 MFD			
Capacitor Catalog Number	7C100M30RA			
Capacitor Requirements	280V			
Capacitor Temperature Rating	105°C			
Capacitor Diameter/Oval Dimensions	1.65 in			
Capacitor Height	2.75 in			
Automatic Restart	No			
Operating and Electrical				
Input Voltage	120/208/240/277 V			

Input Frequency	60 Hz					
Inp. Current (Open Circuit)	2.2/1.25/1.1/0.85 A					
Input Current (Starting)	0.75/0.45/0.37/0.3 A					
Input Current (Short Circuit)	0.6-0.9/0.35-0.55/0.3-0.45/0.29-0.43 A					
Secondary Short Circuit Current	2.6-3.3 A					
onstant Wattage Deviation Within Trapezoid						
Ballast Factor (Nom)	1					
Power Factor (Nom)	0.90					
Nominal Open Circuit Voltage	125 V					
Input Current (Operating) (Nom)	1.15/0.67/0.58/0.5 A A					
Input Power (Nom)	135 W					
Rated Lamp Watts	100 W					
Wiring						
Wire Striplength	0.5 mm					
Wire Length by Color	12"					
Wire Type	Stranded					
Remote Wiring Configuration Allowed	Yes					
Max Ballast-Lamp Distance Remote	2'					
Wiring						


Datasheet, 2019, February 12 data subject to change

# Core & Coil (71A) HPS ~LT~ 200W

Recommended Fuse Value	7/5/3/3 A				
Approval and Application					
Open Circuit Voltage Test (Volts)	110-130 V				
Approbation Marks	ULR CSA certificate RoHS Compliant				
Temperature Marking	E/F/E/D				
UL Recognized	Yes				
Hipot Test (1 Minute)	2000 V				
Hipot Test (2 Seconds)	2500 V				
UL Insulation Class	H(180°C)				
UL Temperature Code	1029F				

Product Data	
Order product name	CORE & COIL HID HPS BAL 100W S54 QUAD KIT
EAN/UPC - Product	781087077894
Order code	71A8091001DC
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	913700502809
Net Weight (Piece)	3.207 kg

## Dimensional drawing



CORE & COIL HID 71A8091001DC	3.45 in	2 in	3.9 in	3.5 in	2.8 in	2.4 in

C2 A1



Product