

Core & Coil (71A) MH ~LT~ 175W

CORE & COIL HID MH BAL 150W M102/142 120/277/347V C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data


General Information		Operating and Electrical	
ANSI Code	M102-M142	Input Voltage	120/277/347 V
Lamp Type	150 MH	Input Frequency	60 Hz
Number of Lamps	1 piece/unit	Input Current (Open Circuit)	3.65/1.58/1.25 A
Circuit Type	HX-HPF	Input Current (Starting)	0.95/0.42/0.65 A
Ballast Type	Magnetic HID	Input Current (Short Circuit)	1.2-1.9/0.5-0.8/0.45-0.75 A
Base Model	71A54A2	Secondary Short Circuit Current	2.05-2.55 A
Core Size	3 X 4 (2 coil)	Constant Wattage Deviation	12%
Suitable For Outdoor Use	Yes	Ballast Factor (Nom)	1
Ignitor Catalog Number	LI533-H4	Power Factor (Nom)	0.90
Ignitor Temperature Rating	105°C	Open Circuit Voltage	265 V
Capacitor Value	16 MFD	Input Current (Nom)	1.6/0.7/0.55 A A
Capacitor Catalog Number	7C160M30RA	Input Power (Nom)	185 W
Capacitor Requirements	280V	Rated Lamp Power	150 W
Capacitor Temperature Rating	105°C		
Capacitor Diameter/Oval Dimensions	1.65 in	Wiring	
Capacitor Height	2.75 in	Wire Striplength	0.5 mm
Automatic Restart	No	Wire Length by Color	12"
		Wire Type	Stranded
		Remote Wiring Configuration Allowed	Yes

Core & Coil (71A) MH ~LT~ 175W

Max Ballast-Lamp Distance Remote Wiring 10'	
Recommended Fuse Value	10/4/3 A
Approval and Application	
Open Circuit Voltage Test (Volts)	235-290 V
Approval Marks	ULR CSA certificate RoHS Compliant
Temperature Marking	E/E/E
UL Recognized	Yes
Hipot Test (1 Minute)	2000 V
Hipot Test (2 Seconds)	2500 V
UL Insulation Class	H(180°C)
UL Temperature Code	1029E

Product Data	
Order product name	CORE & COIL HID MH BAL 150W M102/142 120/277/347V C&C
EAN/UPC - Product	781087054529
Order code	177717
Local order code	177717
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	913700502811
Net Weight (Piece)	3.371 kg

Dimensional drawing



MH BAL 150W M102/142 120/277/347V C&C

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 71A54A2510D	3.87 in	2.25 in	3.9 in	3.5 in	2.8 in	2.4 in

