



## Core & Coil (71A) MH 175W - 450W

# CORE & COIL HID MH BAL 175W M57 120/277/347V C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

#### **Product data**

General Information				
ANSI Code	M57-M107			
Lamp Type	175/150W MH			
Number of Lamps	1 piece/unit			
Circuit Type	CWA			
Ballast Type	Magnetic HID			
Base Model	71A55A0			
Core Size	3 X 4 (2 LW)			
Suitable For Outdoor Use	Yes			
Ignitor Catalog Number	NA			
Ignitor Temperature Rating	NA			
Capacitor Value	10 MFD			
Capacitor Catalog Number	7C100M40R			
Capacitor Requirements	400V			
Capacitor Temperature Rating	105°C			
Capacitor Diameter/Oval Dimensions	1.45 in			
Capacitor Height	3.75 in			
Automatic Restart	No			

Operating and Electrical						
Input Voltage	120/277/347 V					
Input Frequency	60 Hz					
Input Current (Open Circuit)	1.91/0.79/0.63 A					
Input Current (Starting)	0.94/0.41/0.33 A					
Input Current (Short Circuit)	0.78-1.17/0.35-0.52/0.25-0.32 A					
Secondary Short Circuit Current	1.51-1.85 A					
Constant Wattage Deviation	10%					
Ballast Factor (Nom)	1					
Power Factor (Nom)	0.90					
Open Circuit Voltage	305 V					
Input Current (Nom)	1.8/0.8/0.62 A A					
Input Power (Nom)	213 W					
Rated Lamp Power	175/150 W					
Wiring						
Wire Striplength	0.5 mm					
Wire Length by Color	12"					
Wire Type	Stranded					
Remote Wiring Configuration Allowed	Yes					


Datasheet, 2019, February 12 data subject to change

### Core & Coil (71A) MH 175W - 450W

Max Ballast-Lamp Distance Remote	Determined by AWG used				
Wiring					
Recommended Fuse Value	5/3/2 A				
Approval and Application					
Open Circuit Voltage Test (Volts)	275-337 V				
Approval Marks	ULR CSA certificate RoHS Compliant				
Temperature Marking	C/C/D				
UL Recognized	Yes				
Hipot Test (1 Minute)	2000 V				
Hipot Test (2 Seconds)	2500 V				
UL Insulation Class	H(180°C)				
UL Temperature Code	1029D				

Product Data	
Order product name	CORE & COIL HID MH BAL 175W M57
	120/277/347V C&C
EAN/UPC - Product	781087018378
Order code	177971
Local order code	177971
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	913700503091
Net Weight (Piece)	3.062 kg

#### Dimensional drawing



MH BAL 175W M57 120/277/347V C&C

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 71A55A0600	4.02 in	2.41 in	3.9 in	3.5 in	2.8 in	2.4 in

