



# Core & Coil (71A) MH ~GT~ 450W

# CORE & COIL HID MH BAL 1000W M47 QUAD C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

### **Product data**

General Information					
ANSI Code	M47				
Lamp Type	1000W MH				
Number of Lamps	1 piece/unit				
Circuit Type	CWA				
Ballast Type	Magnetic HID				
Base Model	71A6592				
Core Size	4 1/4 x 6 (2 Coil)				
Suitable For Outdoor Use	Yes				
Ignitor Catalog Number	NA				
Ignitor Temperature Rating	NA				
Capacitor Value	24 MFD				
Capacitor Catalog Number	MD2409000				
Capacitor Requirements	480V				
Capacitor Temperature Rating	90°C				
Capacitor Diameter/Oval Dimensions	1.75 in				
Capacitor Height	3.9 in				
Automatic Restart	No				
Operating and Electrical					
Input Voltage	120/208/240/277 V				

Input Frequency	60 Hz
Input Current (Open Circuit)	4.5/2.7/2.3/2.2 A
Input Current (Starting)	7.8/4/3.7/3.2 A
Input Current (Short Circuit)	5.6-8.6/3.2-4.8/2.8-4.3/2.4-3.6 V
Secondary Short Circuit Current	5.2-6.4 A
Constant Wattage Deviation	10%
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Open Circuit Voltage	430 V
Input Current (Nom)	9/5.2/4.5/3.9 A A
Input Power (Nom)	1080 W
Rated Lamp Power	1000 W
Wiring	
Wire Striplength	0.5 mm
Wire Length by Color	12"
Wire Type	Stranded
Remote Wiring Configuration Allowed	Yes
Max Ballast-Lamp Distance Remote	Determined by AWG used
Wiring	


Datasheet, 2019, February 12 data subject to change

# Core & Coil (71A) MH ~GT~ 450W

Recommended Fuse Value	20/15/10/10 A					
Approval and Application						
Open Circuit Voltage Test (Volts)	385-475 V					
Approval Marks	ULR CSA certificate RoHS Compliant					
Temperature Marking	A/A/A/A					
UL Recognized	Yes					
Hipot Test (1 Minute)	2000 V					
Hipot Test (2 Seconds)	2500 V					
UL Insulation Class	N(AC200°C)					
UL Temperature Code	1029A					

Product Data					
Order product name	CORE & COIL HID MH BAL 1000W M47 QUAD				
	C&C				
EAN/UPC - Product	781087022634				
Order code	913700504241				
Numerator - Quantity Per Pack	1				
Numerator - Packs per outer box	2				
Material Nr. (12NC)	913700504241				
Net Weight (Piece)	8.669 kg				

## Dimensional drawing



MH BAL 1000W M47 QUAD C&C

Product	C1	C2	A1	A2	А3	B1	B2
CORE & COIL HID 71A6592600	4.5 in	2.57 in	6 in	5.4 in	4.4 in	4.3 in	3.9 in

