



# Core & Coil (71A) HPS ~LT~ 200W

## CORE & COIL HID HPS BAL 70W S62 120/277V C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

#### **Product data**

General Information	
ANSI Code	S62
Lamp Type	70W HPS
Number of Lamps	1 piece/unit
Circuit Type	CWA
Ballast Type	Magnetic HID
Base Model	71A7988
Core Size	3 X 4 (2 coil)
Suitable For Outdoor Use	Yes
Ignitor Catalog Number	LI551-J4
Ignitor Temperature Rating	105°C
Capacitor Value	28 MFD
Capacitor Catalog Number	7C280P30RA
Capacitor Requirements	170V
Capacitor Temperature Rating	105°C
Capacitor Diameter/Oval Dimensions	1.85 in
Capacitor Height	3.7 in
Automatic Restart	No


Operating and Electrical	
Input Voltage	120/277 V
Input Frequency	60 Hz
Inp. Current (Open Circuit)	0.18/0.08 A
Input Current (Starting)	0.85/0.36 A
Input Current (Short Circuit)	0.7-1.1/0.3-0.5 A
Secondary Short Circuit Current	2.0-2.6 A
Constant Wattage Deviation	Within Trapezoid
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Nominal Open Circuit Voltage	105 V
Input Current (Operating) (Nom)	0.85/0.36 A A
Input Power (Nom)	95 W
Rated Lamp Watts	70 W
Wiring	
Wire Striplength	0.5 mm
Wire Length by Color	12"
Wire Type	Stranded
Remote Wiring Configuration Allowed	Yes

### Core & Coil (71A) HPS ~LT~ 200W


Max Ballast-Lamp Distance Remote V	Viring 5'
Recommended Fuse Value	3/1 A
Approval and Application	
Open Circuit Voltage Test (Volts)	95-115 V
Approbation Marks	ULR CSA certificate RoHS Compliant
Temperature Marking	A/D
UL Recognized	Yes
Hipot Test (1 Minute)	2000 V
Hipot Test (2 Seconds)	2500 V
UL Insulation Class	H(180°C)
UL Temperature Code	1029D

Product Data	
Order product name	CORE & COIL HID HPS BAL 70W S62
	120/277V C&C
EAN/UPC - Product	781087798850
Order code	71A7988500D
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	913700504621
Net Weight (Piece)	2.559 kg

#### **Dimensional drawing**



HPS BAL 70W S62 120/277V C&C





© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2019, February 12 - data subject to change