



Core & Coil (71A) MH 175W - 450W

CORE & COIL HID MH BAL 400W M59 QUAD KIT

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information	
ANSI Code	M59
Lamp Type	400W MH
Number of Lamps	1 piece/unit
Circuit Type	CWA
Ballast Type	Magnetic HID
Base Model	71A6071
Core Size	4 1/4 x 4 3/4 (2 coil)
Suitable For Outdoor Use	Yes
Ignitor Catalog Number	NA
Ignitor Temperature Rating	NA
Capacitor Value	24 MFD
Capacitor Catalog Number	7C240P40R
Capacitor Requirements	400V
Capacitor Temperature Rating	105°C
Capacitor Diameter/Oval Dimensions	1.75 in
Capacitor Height	4.8 in
Automatic Restart	No
Operating and Electrical	
Input Voltage	120/208/240/277 V

Input Current (Open Circuit) 3/1.8/1.5/1.35 A Input Current (Starting) 3.25/1.9/1.65/1.45 A Input Current (Short Circuit) 2.54-3.81/1.46-2.19/1.27-1.9/1.1-1.66 A Secondary Short Circuit Current 3.43-4.19 A Constant Wattage Deviation 10% Ballast Factor (Nom) 0 Open Circuit Voltage 305 V Input Current (Nom) 4/2.3/2/1.72 A A Input Power (Nom) 455 W Rated Lamp Power 400 W Wiring Wire Striplength 0.5 mm Wire Length by Color 12" Wire Type Stranded Remote Wiring Configuration Allowed Yes Max Ballast-Lamp Distance Remote Determined by AWG used	Input Frequency	60 Hz
Input Current (Short Circuit) 2.54-3.81/1.46-2.19/1.27-1.9/1.1-1.66 A Secondary Short Circuit Current 3.43-4.19 A Constant Wattage Deviation 10% Ballast Factor (Nom) 1 Power Factor (Nom) 0.90 Open Circuit Voltage 305 V Input Current (Nom) 4/2.3/2/1.72 A A Input Power (Nom) 455 W Rated Lamp Power 400 W Wiring Wire Striplength 0.5 mm Wire Length by Color 12" Wire Type Stranded Remote Wiring Configuration Allowed Yes Max Ballast-Lamp Distance Remote Determined by AWG used	Input Current (Open Circuit)	3/1.8/1.5/1.35 A
Secondary Short Circuit Current 3.43-4.19 A Constant Wattage Deviation 10% Ballast Factor (Nom) 1 Power Factor (Nom) 0.90 Open Circuit Voltage 305 V Input Current (Nom) 4/2.3/2/1.72 A A Input Power (Nom) 455 W Rated Lamp Power 400 W Wiring Wire Striplength 0.5 mm Wire Length by Color 12" Wire Type Stranded Remote Wiring Configuration Allowed Yes Max Ballast-Lamp Distance Remote Determined by AWG used	Input Current (Starting)	3.25/1.9/1.65/1.45 A
Constant Wattage Deviation 10% Ballast Factor (Nom) 1 Power Factor (Nom) 0.90 Open Circuit Voltage 305 V Input Current (Nom) 4/2.3/2/1.72 A A Input Power (Nom) 455 W Rated Lamp Power 400 W Wiring Wire Striplength 0.5 mm Wire Length by Color 12" Wire Type Stranded Remote Wiring Configuration Allowed Yes Max Ballast-Lamp Distance Remote Determined by AWG used	Input Current (Short Circuit)	2.54-3.81/1.46-2.19/1.27-1.9/1.1-1.66 A
Ballast Factor (Nom) 1 Power Factor (Nom) 0.90 Open Circuit Voltage 305 V Input Current (Nom) 4/2.3/2/1.72 A A Input Power (Nom) 455 W Rated Lamp Power 400 W Wiring Wire Striplength 0.5 mm Wire Length by Color 12" Wire Type Stranded Remote Wiring Configuration Allowed Yes Max Ballast-Lamp Distance Remote Determined by AWG used	Secondary Short Circuit Current	3.43-4.19 A
Power Factor (Nom) Open Circuit Voltage 305 V Input Current (Nom) 4/2.3/2/1.72 A A Input Power (Nom) 455 W Rated Lamp Power 400 W Wiring Wire Striplength 0.5 mm Wire Length by Color 12" Wire Type Stranded Remote Wiring Configuration Allowed Yes Max Ballast-Lamp Distance Remote Determined by AWG used	Constant Wattage Deviation	10%
Open Circuit Voltage 305 V Input Current (Nom) 4/2.3/2/1.72 A A Input Power (Nom) 455 W Rated Lamp Power 400 W Wiring Wire Striplength 0.5 mm Wire Length by Color 12" Wire Type Stranded Remote Wiring Configuration Allowed Yes Max Ballast-Lamp Distance Remote Determined by AWG used	Ballast Factor (Nom)	1
Input Current (Nom) 4/2.3/2/1.72 A A Input Power (Nom) 455 W Rated Lamp Power 400 W Wiring Wire Striplength 0.5 mm Wire Length by Color 12" Wire Type Stranded Remote Wiring Configuration Allowed Yes Max Ballast-Lamp Distance Remote Determined by AWG used	Power Factor (Nom)	0.90
Input Power (Nom) 455 W Rated Lamp Power 400 W Wiring Wire Striplength 0.5 mm Wire Length by Color 12" Wire Type Stranded Remote Wiring Configuration Allowed Yes Max Ballast-Lamp Distance Remote Determined by AWG used	Open Circuit Voltage	305 V
Rated Lamp Power 400 W Wiring Wire Striplength 0.5 mm Wire Length by Color 12" Wire Type Stranded Remote Wiring Configuration Allowed Yes Max Ballast-Lamp Distance Remote Determined by AWG used	Input Current (Nom)	4/2.3/2/1.72 A A
Wire Striplength 0.5 mm Wire Length by Color 12" Wire Type Stranded Remote Wiring Configuration Allowed Yes Max Ballast-Lamp Distance Remote Determined by AWG used	Input Power (Nom)	455 W
Wire Striplength 0.5 mm Wire Length by Color 12" Wire Type Stranded Remote Wiring Configuration Allowed Yes Max Ballast-Lamp Distance Remote Determined by AWG used	Rated Lamp Power	400 W
Wire Striplength 0.5 mm Wire Length by Color 12" Wire Type Stranded Remote Wiring Configuration Allowed Yes Max Ballast-Lamp Distance Remote Determined by AWG used		
Wire Length by Color 12" Wire Type Stranded Remote Wiring Configuration Allowed Yes Max Ballast-Lamp Distance Remote Determined by AWG used	Wiring	
Wire Type Stranded Remote Wiring Configuration Allowed Yes Max Ballast-Lamp Distance Remote Determined by AWG used	Wire Striplength	0.5 mm
Remote Wiring Configuration Allowed Yes Max Ballast-Lamp Distance Remote Determined by AWG used	Wire Length by Color	12"
Max Ballast-Lamp Distance Remote Determined by AWG used	Wire Type	Stranded
	Remote Wiring Configuration Allowed	Yes
Wiring	Max Ballast-Lamp Distance Remote	Determined by AWG used
	Wiring	


Datasheet, 2019, March 22 data subject to change

Core & Coil (71A) MH 175W - 450W

Recommended Fuse Value	10/7/5/5 A
Approval and Application	
Open Circuit Voltage Test (Volts)	275-335 V
Approval Marks	ULR CSA certificate RoHS Compliant
Temperature Marking	D/E/D/E
UL Recognized	Yes
Hipot Test (1 Minute)	2000 V
Hipot Test (2 Seconds)	2500 V
UL Insulation Class	H(180°C)
UL Temperature Code	1029E

Product Data	
Order product name	CORE & COIL HID MH BAL 400W M59 QUAD KIT
EAN/UPC - Product	781087096499
Order code	191882
Local order code	191882
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	913700525409
Net Weight (Piece)	5.421 kg

Dimensional drawing



MH BAL 400W M59 QUAD KIT

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID MH BAL 400W M59	4 in	2.13 in	4.8 in	4.4 in	4.3 in	3.9 in
QUAD KIT						

