Core & Coil (71A) HPS ~LT~ 200W

CORE & COIL HID HPS BAL 70W S62 120V C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information

ANSI Code	S62
Lamp Type	70W HPS
Number of Lamps	1 piece/unit
Circuit Type	R-HPF
Ballast Type	Magnetic HID
Base Model	71A7907B
Core Size	2 5/8 x 2 3/16
Suitable For Outdoor Use	Yes
Ignitor Catalog Number	INTEGRAL
Ignitor Temperature Rating	125℃
Capacitor Value	28 MFD
Capacitor Catalog Number	7C280M12RA
Capacitor Requirements	120V
Capacitor Temperature Rating	105℃
Capacitor Diameter/Oval Dimensions	1.65 in
Capacitor Height	2.75 in
Automatic Restart	No

Operating and Electrical

Input Voltage	120 V
Input Frequency	60 Hz
Inp. Current (Open Circuit)	1.3 A
Input Current (Starting)	0.9 A
Input Current (Short Circuit)	1.9-2.9 A
Secondary Short Circuit Current	1.9-2.9 A
Constant Wattage Deviation	Within Trapezoid
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Nominal Open Circuit Voltage	120 V
Input Current (Operating) (Nom)	0.75 A A
Input Power (Nom)	86 W
Rated Lamp Watts	70 W

Wiring

Wire Striplength	0.5 mm
Wire Length by Color	12"
Wire Type	Stranded
Remote Wiring Configuration Allowed	Yes
Max Ballast-Lamp Distance Remote Wiring	2'
Recommended Fuse Value	3 A

# Core & Coil (71A) HPS ~LT~ 200W

Approval and Application

Open Circuit Voltage Test (Volts)	114–126 V
Approbation Marks	ULR CSA certificate RoHS Compliant
Temperature Marking	A
UL Recognized	Yes
Hipot Test (1 Minute)	2000 V
Hipot Test (2 Seconds)	2500 V
UL Insulation Class	H(180°C)
UL Temperature Code	1029A

Product Data

Order product name	CORE & COIL HID HPS BAL 70W S62 120V C&C

EAN/UPC – Product	781087790748
Order code	71A7907500DB
Numerator – Quantity Per Pack	1
Numerator – Packs per outer box	16
Material Nr. (12NC)	913700525809
Net Weight (Piece)	0.994 kg

Dimensional drawing

HPS BAL 70W S62 120V C&C

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 71A7907500DB	2.9 in	1.3 in	2.6 in	2.2 in	2.2 in	1.8 in

www.lighting.philips.com

2019, February 12 – data subject to change