



# **SmartMate**

## SMARTMATE ELE BALLAST (2) 13W CFL (4-PIN) 120-277V

Offering maximum versatility, the Philips Advance family of SmartMate ballasts for 4-pin compact fluorescent lamps drive a broad range of quad and triple-tube, circline, 2D, and long twin-tube lamps. SmartMate ballasts' energy efficient design, compact and lightweight housing, and user-friendly features make these ballasts an ideal choice for fixture manufacturers, retrofitters, and MRO replacement.

#### **Product data**

General Information				
Lamp Type	CFQ13W/G24Q			
Number of Lamps	1/2 piece/unit			
Ballast Type	Electronic Fluorescent			
Base Model	ICF2S13M1BS			
Suitable For Outdoor Use	Yes			
Automatic Restart	Yes			
Operating and Electrical				
Input Voltage	120 to 277 V			
Input Frequency	50 to 60 Hz			
Total Harmonic Distortion USA	10 %			
Ignition Method	Programmed Start			
Crestfactor (Nom)	1.5			
Ignition Time (Nom)	1.5 s			
Ballast Factor (Nom)	1			
Power Factor (Nom)	0.98			
Input Current (Max)	0.25 A			
Input Current (Min)	0.11 A			
Input Power (Nom)	29-29 W			


Rated Lamp Power	13 W
Wiring	
wiring	
Color Input Terminals	Black and White
Color Output Terminals	RED, YEL & BLU
Wire Striplength	0.375 mm
Lamp Connection	Series
Wire Length by Color	No wires
Wire Gauge (Nom)	18AWG mm
Wire Type	Solid
Remote Wiring Configuration Allowed	Yes
Tandem Wiring Configuration Allowed	Yes
Through Wiring Configuration Allowed	Yes
Max Ballast-Lamp Distance Remote Wiring	1-L = 15' / 2-L = 6'
Max Ballast-Lamp Distance Tandem Wiring	2-L: Red = 6'
Max Ballast-Lamp Distance Through Wiring	2-L: Red = 6'
Connector Type	Poke-In
Temperature	
T-Case Maximum (Nom)	75 ℃
	75 ℃

### **SmartMate**

Mechanical and Housing	
Housing Material	Metal-Plastic
Housing	H1
Housing Dimensions	4.98" x 2.4" x 0.98"
Approval and Application	
EMC Immunity Standard	FCC Non-Consumer
Approval Marks	CSA certificate UL certificate CEC Listing
	NOM certificate RoHS Compliant
Hum And Noise Level	A
UL Recognized	No

Order product name SMARTMATE ELE BALLAST (2) 13W CI   PIN) 120-277V PIN) 120-277V   EAN/UPC - Product 781087104101   Order code 913700532201   Numerator - Quantity Per Pack 1   Numerator - Packs per outer box 16	
EAN/UPC - Product     781087104101       Order code     913700532201       Numerator - Quantity Per Pack     1	L (4-
Order code     913700532201       Numerator - Quantity Per Pack     1	
Numerator - Quantity Per Pack 1	
· · ·	
Numerator - Packs per outer box 16	
Material Nr. (12NC) 913700532201	
Net Weight (Piece) 0.209 kg	

#### Dimensional drawing



Product	A1	A2	A3	B1	C1
SMARTMATE ELE BALLAST (2) 13W	4.60 in	4.20 in	2.00 in	2.40 in	0.98 in
CFL (4-PIN) 120-277V					



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.