



Core & Coil (71A) MH ~LT~ 175W

CORE & COIL HID MH BAL 100W M90/140 277V C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

| General Information | |
|------------------------------------|----------------|
| ANSI Code | M90-M140 |
| Lamp Type | 100W MH |
| Number of Lamps | 1 piece/unit |
| Circuit Type | R-HPF |
| Ballast Type | Magnetic HID |
| Base Model | 71A5337BP |
| Core Size | 2 5/8 x 2 3/16 |
| Suitable For Outdoor Use | Yes |
| Ignitor Catalog Number | INTEGRAL |
| Ignitor Temperature Rating | 125°C |
| Capacitor Value | 10 MFD |
| Capacitor Catalog Number | 7C100M30RA |
| Capacitor Requirements | 280V |
| Capacitor Temperature Rating | 105°C |
| Capacitor Diameter/Oval Dimensions | 1.65 in |
| Capacitor Height | 2.75 in |
| Automatic Restart | No |
| | |

| Operating and Electrical | |
|-------------------------------------|-------------|
| Input Voltage | 277 V |
| Input Frequency | 60 Hz |
| Input Current (Open Circuit) | 1.05 A |
| Input Current (Starting) | 0.7 A |
| Input Current (Short Circuit) | 0.25-0.35 A |
| Secondary Short Circuit Current | 1.05-1.55 A |
| Constant Wattage Deviation | 10% |
| Ballast Factor (Nom) | 1 |
| Power Factor (Nom) | 0.90 |
| Open Circuit Voltage | 277 V |
| Input Current (Nom) | 0.45 A A |
| Input Power (Nom) | 118 W |
| Rated Lamp Power | 100 W |
| | |
| Wiring | |
| Wire Striplength | 0.5 mm |
| Wire Length by Color | 12" |
| Wire Type | Stranded |
| Remote Wiring Configuration Allowed | Yes |


Datasheet, 2019, March 22 data subject to change

Core & Coil (71A) MH ~LT~ 175W

| Max Ballast-Lamp Distance Remote Wiring 2' | | |
|--|--------------------------------|--|
| Recommended Fuse Value | 3 A | |
| | | |
| Approval and Application | | |
| Open Circuit Voltage Test (Volts) | 260-290 V | |
| Approval Marks | RoHS Compliant CSA certificate | |
| emperature Marking | А | |
| JL Recognized | Yes | |
| lipot Test (1 Minute) | 2000 V | |
| lipot Test (2 Seconds) | 2500 V | |
| JL Insulation Class | H(180°C) | |
| JL Temperature Code | 1029A | |

| Product Data | |
|---------------------------------|-------------------------------------|
| Order product name | CORE & COIL HID MH BAL 100W M90/140 |
| | 277V C&C |
| EAN/UPC - Product | 781087097625 |
| Order code | 192849 |
| Local order code | 192849 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 16 |
| Material Nr. (12NC) | 913700532209 |
| Net Weight (Piece) | 1.411 kg |

Dimensional drawing



MH BAL 100W M90/140 277V C&C

 Product
 C1
 C2
 A1
 A2
 B1
 B2

 CORE & COIL HID MH BAL 100W M90/140
 3.1 in
 1.8 in
 2.6 in
 2.2 in
 2.2 in
 1.8 in

 277V C&C

