



# Core & Coil (71A) MH ~LT~ 175W

## CORE & COIL HID MH BAL 100W M90/140 277V C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

#### **Product data**

General Information				
ANSI Code	M90-M140			
Lamp Type	100W MH			
Number of Lamps	1 piece/unit			
Circuit Type	R-HPF			
Ballast Type	Magnetic HID			
Base Model	71A5337P			
Core Size	2 5/8 x 2 3/16			
Suitable For Outdoor Use	Yes			
Ignitor Catalog Number	LI533-H4			
Ignitor Temperature Rating	105°C			
Capacitor Value	10 MFD			
Capacitor Catalog Number	7C100M30RA			
Capacitor Requirements	280V			
Capacitor Temperature Rating	105°C			
Capacitor Diameter/Oval Dimensions	1.65 in			
Capacitor Height	2.75 in			
Automatic Restart	No			

Operating and Electrical					
Input Voltage	277 V				
Input Frequency	60 Hz				
Input Current (Open Circuit)	1.05 A				
Input Current (Starting)	0.7 A				
Input Current (Short Circuit)	0.25-0.35 A				
Secondary Short Circuit Current	1.05-1.55 A				
Constant Wattage Deviation	10%				
Ballast Factor (Nom)	1				
Power Factor (Nom)	0.90				
Open Circuit Voltage	277 V				
Input Current (Nom)	0.45 A A				
Input Power (Nom)	118 W				
Rated Lamp Power	100 W				
Wiring					
Wire Striplength	0.5 mm				
Wire Length by Color	12"				
Wire Type	Stranded				
Remote Wiring Configuration Allowed	Yes				


Datasheet, 2019, February 12 data subject to change

### Core & Coil (71A) MH ~LT~ 175W

Max Ballast-Lamp Distance Remote Wiring 2'					
Recommended Fuse Value	3 A				
Approval and Application					
Open Circuit Voltage Test (Volts)	260-290 V				
Approval Marks	ULR CSA certificate RoHS Compliant				
Temperature Marking	А				
UL Recognized	Yes				
Hipot Test (1 Minute)	2000 V				
Hipot Test (2 Seconds)	2500 V				
UL Insulation Class	H(180°C)				
UL Temperature Code	1029A				
	1				

Product Data					
Order product name	CORE & COIL HID MH BAL 100W M90/140				
	277V C&C				
EAN/UPC - Product	781087097618				
Order code	913700532609				
Numerator - Quantity Per Pack	1				
Numerator - Packs per outer box	12				
Material Nr. (12NC)	913700532609				
Net Weight (Piece)	1.348 kg				

#### Dimensional drawing



MH BAL 100W M90/140 127/220V C&C

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 71A5337500DP	2.75 in	1.65 in	2.6 in	2.2 in	2.2 in	1.8 in

