



Core & Coil (71A) HPS ~LT~ 200W

CORE & COIL HID HPS BAL 50W S68 120V C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

| General Information | |
|------------------------------------|----------------|
| ANSI Code | S68 |
| Lamp Type | 50W HPS |
| Number of Lamps | 1 piece/unit |
| Circuit Type | R-HPF |
| Ballast Type | Magnetic HID |
| Base Model | 71A7807B |
| Core Size | 2 5/8 x 2 3/16 |
| Suitable For Outdoor Use | Yes |
| Ignitor Catalog Number | INTEGRAL |
| Ignitor Temperature Rating | 125°C |
| Capacitor Value | 20 MFD |
| Capacitor Catalog Number | 7C200M12RA |
| Capacitor Requirements | 120V |
| Capacitor Temperature Rating | 105°C |
| Capacitor Diameter/Oval Dimensions | 1.25 in |
| Capacitor Height | 2.75 in |
| Automatic Restart | No |
| | |
| Operating and Electrical | |
| Input Voltage | 120 V |
| | |

| Input Frequency | 60 Hz | |
|--|------------------|--|
| Input Current (Open Circuit) | 0.9 A | |
| Input Current (Starting) | 0.95 A | |
| Input Current (Short Circuit) | 1.45-2.2 A | |
| Secondary Short Circuit Current | 1.45-2.2 A | |
| Constant Wattage Deviation | Within Trapezoid | |
| Ballast Factor (Nom) | 1 | |
| Power Factor (Nom) | 0.90 | |
| Open Circuit Voltage | 120 V | |
| Input Current (Nom) | 0.55 A A | |
| Input Power (Nom) | 62 W | |
| Rated Lamp Power | 50 W | |
| | | |
| Wiring | | |
| Wire Striplength | 0.5 mm | |
| Wire Length by Color | 12" | |
| Wire Type | Stranded | |
| Remote Wiring Configuration Allowed | Yes | |
| Max Ballast-Lamp Distance Remote Wiring 2' | | |
| Recommended Fuse Value | 3 A | |
| | | |


Datasheet, 2019, February 12 data subject to change

Core & Coil (71A) HPS ~LT~ 200W

| Approval and Application | | | | | |
|-----------------------------------|--------------------------------------|--|--|--|--|
| Open Circuit Voltage Test (Volts) | 114-126 V | | | | |
| Approval Marks | ULR CSA certificate RoHS Compliant | | | | |
| Temperature Marking | А | | | | |
| UL Recognized | Yes | | | | |
| Hipot Test (1 Minute) | 2000 V | | | | |
| Hipot Test (2 Seconds) | 2500 V | | | | |
| UL Insulation Class | H(180°C) | | | | |
| UL Temperature Code | 1029A | | | | |
| | | | | | |
| Product Data | | | | | |
| Order product name | CORE & COIL HID HPS BAL 50W S68 120V | | | | |
| | C&C | | | | |

| EAN/UPC - Product | 781087780749 |
|---------------------------------|--------------|
| Order code | 193326 |
| Local order code | 193326 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 8 |
| Material Nr. (12NC) | 913700537809 |
| Net Weight (Piece) | 0.704 kg |
| | |

Dimensional drawing



HPS BAL 50W S68 120V C&C

| Product | C1 | C2 | A1 | A2 | B1 | B2 |
|------------------------------|--------|---------|--------|--------|--------|--------|
| CORE & COIL HID 71A7807500DB | 2.7 in | 0.95 in | 2.6 in | 2.2 in | 2.2 in | 1.8 in |

