



# Core & Coil (71A) HPS ~LT~ 200W

### CORE & COIL HID HPS BAL 50W S68 120V C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

#### **Product data**

General Information				
ANSI Code	S68			
Lamp Type	50W HPS			
Number of Lamps	1 piece/unit			
Circuit Type	R-HPF			
Ballast Type	Magnetic HID			
Base Model	71A7807			
Core Size	2 5/8 x 2 3/16			
Suitable For Outdoor Use	Yes			
Ignitor Catalog Number	LI551-H4			
Ignitor Temperature Rating	105°C			
Capacitor Value	20 MFD			
Capacitor Catalog Number	7C200M12RA			
Capacitor Requirements	120V			
Capacitor Temperature Rating	105°C			
Capacitor Diameter/Oval Dimensions	1.25 in			
Capacitor Height	2.75 in			
Automatic Restart	No			
Operating and Electrical				
Input Voltage	120 V			

Input Frequency	60 Hz			
Inp. Current (Open Circuit)	0.9 A			
Input Current (Starting)	0.95 A			
Input Current (Short Circuit)	1.45-2.2 A			
Secondary Short Circuit Current	1.45-2.2 A			
Constant Wattage Deviation	Within Trapezoid			
Ballast Factor (Nom)	1			
Power Factor (Nom)	0.90			
Nominal Open Circuit Voltage	120 V			
Input Current (Operating) (Nom)	0.55 A A			
Input Power (Nom)	62 W			
Rated Lamp Watts	50 W			
Wiring				
Wire Striplength	0.5 mm			
Wire Length by Color	12"			
Wire Type	Stranded			
Remote Wiring Configuration Allowed	Yes			
Max Ballast-Lamp Distance Remote Wiring 2'				
Recommended Fuse Value	3 A			


Datasheet, 2019, February 12 data subject to change

# Core & Coil (71A) HPS ~LT~ 200W

Approval and Application					
Open Circuit Voltage Test (Volts)	114-126 V				
Approbation Marks	ULR CSA certificate RoHS Compliant				
Temperature Marking	A				
UL Recognized	Yes				
Hipot Test (1 Minute)	2000 V				
Hipot Test (2 Seconds)	2500 V				
UL Insulation Class	H(180°C)				
UL Temperature Code	1029A				
Product Data					
Order product name	CORE & COIL HID HPS BAL 50W S68 120V				
	C&C				

EAN/UPC - Product	781087780756			
Order code	71A7807500D			
Numerator - Quantity Per Pack	1			
Numerator - Packs per outer box	8			
Material Nr. (12NC)	913700575609			
Net Weight (Piece)	749.000 g			

## Dimensional drawing



HPS BAL 50W S68 120V C&C

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 71A7807500D	2.3 in	0.95 in	2.6 in	2.2 in	2.2 in	1.8 in

