



# Core & Coil (71A) HPS ~GT~ 400W

## CORE & COIL HID HPS BAL 600W S106 120/208/240V C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

#### **Product data**

General Information					
ANSI Code	S106				
Lamp Type	600W HPS				
Number of Lamps	1 piece/unit				
Circuit Type	CWA				
Ballast Type	Magnetic HID				
Base Model	71A85E5				
Core Size	4 1/4 x 6				
Suitable For Outdoor Use	Yes				
Ignitor Catalog Number	LI561-H5				
Ignitor Temperature Rating	105°C				
Capacitor Value	64 MFD				
Capacitor Catalog Number	7C640S28RA				
Capacitor Requirements	280V				
Capacitor Temperature Rating	105°C				
Capacitor Diameter/Oval Dimensions	3.15 in				
Capacitor Height	5.10 in				
Automatic Restart	No				

Operating and Electrical					
Input Voltage	120/208/240 V				
Input Frequency	60 Hz				
Input Current (Open Circuit)	3/1.75/1.6 A				
Input Current (Starting)	5.25/3/2.6 A				
Input Current (Short Circuit)	3.3-5/1.9-2.8/1.6-2.4 A				
Secondary Short Circuit Current	7.4-9 A				
Constant Wattage Deviation	Within Trapezoid				
Ballast Factor (Nom)	1				
Power Factor (Nom)	0.90				
Open Circuit Voltage	220 V				
Input Current (Nom)	5.5/3.25/2.85 A A				
Input Power (Nom)	670 W				
Rated Lamp Power	600 W				
Wiring					
Wire Striplength	0.5 mm				
Wire Length by Color	12"				
Wire Type	Stranded				
Remote Wiring Configuration Allowed	Yes				


Datasheet, 2019, March 22 data subject to change

### Core & Coil (71A) HPS ~GT~ 400W

Max Ballast-Lamp Distance Remote Wiring 2'					
Recommended Fuse Value	15/9/8 A				
Approval and Application					
Open Circuit Voltage Test (Volts)	200-245 V				
Approval Marks	ULR CSA certificate RoHS Compliant				
Temperature Marking	A/A/B				
UL Recognized	Yes				
Hipot Test (1 Minute)	2000 V				
Hipot Test (2 Seconds)	2500 V				
UL Insulation Class	H(180°C)				
UL Temperature Code	1029B				

Product Data					
Order product name	CORE & COIL HID HPS BAL 600W S106				
	120/208/240V C&C				
EAN/UPC - Product	781087042670				
Order code	506600				
Local order code	506600				
Numerator - Quantity Per Pack	1				
Numerator - Packs per outer box	2				
Material Nr. (12NC)	913700578109				
Net Weight (Piece)	10.575 kg				

#### Dimensional drawing



HPS BAL 600W S106 120/208/240V C&C

Product	C1	C2	A1	A2	А3	B1	B2
CORE & COIL HID HPS BAL 600W	5.10 in	3.15 in	6 in	5.4 in	4.4 in	4.3 in	3.9 in
S106 120/208/240V C&C							

