



Outdoor Weatherproof (79W)

OUTDOOR WEATHERPROOF HID MH BAL 400W M59 QUAD WP

Outdoor weatherproof ballasts are designed for remote mounting outdoors under all weather conditions. They may also be placed inside a pole base, but care must be taken to avoid areas prone to flood situations as they are not water submersable.

Product data

General Information	
ANSI Code	M59
Lamp Type	МН
Number of Lamps	1 piece/unit
Circuit Type	CWA
Ballast Type	Magnetic HID
Base Model	79W6091
Suitable For Outdoor Use	Yes
Ignitor Catalog Number	Inside Can
Capacitor Catalog Number	Inside Can
Automatic Restart	No
/ tatomatic restart	···-
Operating and Electrical	
	120/208/240/277 V
Operating and Electrical	120/208/240/277 V 60 Hz
Operating and Electrical Input Voltage	
Operating and Electrical Input Voltage Input Frequency	60 Hz
Operating and Electrical Input Voltage Input Frequency Inp. Current (Open Circuit)	60 Hz 3/1.75/1.5/1.3 A
Operating and Electrical Input Voltage Input Frequency Inp. Current (Open Circuit) Input Current (Starting)	60 Hz 3/1.75/1.5/1.3 A 3.5/2/1.75/1.5 A
Operating and Electrical Input Voltage Input Frequency Inp. Current (Open Circuit) Input Current (Starting) Input Current (Short Circuit)	60 Hz 3/1.75/1.5/1.3 A 3.5/2/1.75/1.5 A 2.7-4.2/1.55-2.4/1.35-2.1/1.1-1.8 A

Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Nominal Open Circuit Voltage	300 V
Input Current (Operating) (Nom)	4/2.3/2/1.75 A A
Input Power (Nom)	458 W
Rated Lamp Watts	400 W
Wiring	
Wire Striplength	0.5 mm
Wire Length by Color	10"
Wire Type	Stranded
Remote Wiring Configuration Allowed	Yes
Max Ballast-Lamp Distance Remote	Determined by AWG used
Wiring	
Recommended Fuse Value	10/7/5/5 A
Mechanical and Housing	
Housing Material	Metal
Housing	OW
	-


Datasheet, 2019, February 12 data subject to change

Outdoor Weatherproof (79W)

Housing Dimensions	8.6" x 6.38" x 6.38"
Approval and Application	
Open Circuit Voltage Test (Volts)	270-330 V
Approbation Marks	CSA certificate UL certificate RoHS Compliant
Temperature Marking	Max. case temperature 90°C
UL Recognized	No
Hipot Test (1 Minute)	2000 V
Hipot Test (2 Seconds)	2500 V
UL Insulation Class	H(180°C)
UL Temperature Code	NA

Product Data	
Order product name	OUTDOOR WEATHERPROOF HID MH BAL
	400W M59 QUAD WP
EAN/UPC - Product	781087960912
Order code	79W6091001
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	913700583809
Net Weight (Piece)	8.605 kg

Dimensional drawing



MH BAL 400W M59 QUAD WP

 Product
 B1
 B2
 B3
 C1
 C2

 OUTDOOR WEATHERPROOF HID 79W6091001
 7.3 in
 6.4 in
 1 in
 8.6 in
 1.9 in



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.