



HID ignitors for MK4 semi-parallel systems

SKD 578-S 220-240V 50/60Hz

HID ignitors for semi-parallel systems


Product data

Operating and Electrical			
Input Voltage	220 to 240 V		
Line Frequency	50 to 60 Hz		
Input Frequency	50 to 60 Hz		
Wiring			
Connector Type	Screw		
Temperature			
Ambient temperature range	-30 °C to 85 °C		
T-Case Maximum (Max)	90 °C		
Approval and Application			
Approval Marks	CE marking ENEC certificate		

Product Data	
Order product name	SKD 578-S 220-240V 50/60Hz
Full product name	SKD 578-S 220-240V 50/60Hz
Full product code	872790089569800
Order code	913700655466
Material Nr. (12NC)	913700655466
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500881779
Numerator - Packs per outer box	20
EAN/UPC - Case	8727900895698

HID ignitors for MK4 semi-parallel systems

Dimensional drawing



Product	A1	B1	C1
SKD 578-S 220-240V 50/60Hz	67.5 mm	40.5 mm	28.0 mm



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2024, February 6 - data subject to change