



PrimaVision Economy for CDM lamps

HID-PV E 50 /S CDM 220-240V


Single CDM lamp operation, single HID electronic gear – improves cost effectiveness and increases luminaire design flexibility

Product data

| Operating and Electrical | | Mechanical and Housing | |
|---|-----------------|---------------------------------|---|
| Input Voltage | 220 to 240 V | Housing | /S |
| Line Frequency | 50 to 60 Hz | | |
| Input Frequency | 50 to 60 Hz | Approval and Application | |
| Inrush Current Width | 0.25 ms | Approval Marks | CE marking ENEC certificate VDE certificate |
| Inrush Current Peak (Max) | 26 A | | |
| Number of Products on MCB (16A Type B) (Nom) | 24 | Product Data | |
| | | Order product name | HID-PV E 50 /S CDM 220-240V |
| | | Full product name | HID-PV E 50 /S CDM 220-240V |
| | | Full product code | 871829121296600 |
| | | Order code | 913700684266 |
| | | Material Nr. (12NC) | 913700684266 |
| | | Numerator - Quantity Per Pack | 1 |
| | | EAN/UPC - Product/Case | 8718291212966 |
| | | Numerator - Packs per outer box | 12 |
| | | EAN/UPC - Case | 8718291212973 |
| Wiring | | | |
| Cable Length From Device to Lamp | 2 m | | |
| Connector Type | Insert | | |
| Temperature | | | |
| Ambient temperature range | -20 °C to 50 °C | | |
| T-Case Lifetime (Nom) | 80 °C | | |
| T-Case Maximum (Max) | 80 °C | | |

PrimaVision Economy for CDM lamps

Dimensional drawing



| Product | D1 | C1 | A1 | A2 | B1 | B2 |
|--------------------------------|--------|---------|----------|---------|---------|---------|
| HID-PV E 50 /S CDM 220-240V | 4.9 mm | 32.2 mm | 109.6 mm | 98.5 mm | 74.4 mm | 63.7 mm |

