



# Core & Coil (71A) HPS 200W - 400W

## **CORE & COIL HID 71A8241500DTA**

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

#### **Product data**

General Information	
ANSI Code	S50
Lamp Type	250W HPS
Number of Lamps	1 piece/unit
Circuit Type	CWA
Ballast Type	Magnetic HID
Base Model	71A8241TA
Core Size	4 x 4 (2 coil)
Suitable For Outdoor Use	Yes
Ignitor Catalog Number	LI501-H4
Ignitor Temperature Rating	105°C
Capacitor Value	35 MFD
Capacitor Catalog Number	7C350P24RA
Capacitor Requirements	240V
Capacitor Temperature Rating	105°C
Capacitor Diameter/Oval Dimensions	1.65 in
Capacitor Height	3.7 in
Automatic Restart	No
Operating and Electrical	
Input Voltage	480/120T V
	,

input Frequency	60 HZ
Input Current (Open Circuit)	0.42 A
Input Current (Starting)	0.38 A
Input Current (Short Circuit)	0.26-0.39 A
Secondary Short Circuit Current	3.65-4.45 A
Constant Wattage Deviation	Within Trapezoid
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Open Circuit Voltage	189 V
Input Current (Nom)	0.63 A A
Input Power (Nom)	299 W
Rated Lamp Power	250 W
Wiring	
Wire Striplength	0.5 mm
Wire Length by Color	12"
Wire Type	Stranded
Remote Wiring Configuration Allowed	Yes
Max Ballast-Lamp Distance Remote Wiring	2'
Recommended Fuse Value	10/4/4/3/2 A

60 Hz

Datasheet, 2019, February 12 data subject to change


Input Frequency

# Core & Coil (71A) HPS 200W - 400W

Approval and Application	
Open Circuit Voltage Test (Volts)	167-203 V
Approval Marks	ULR CSA certificate RoHS Compliant
Temperature Marking	В
UL Recognized	Yes
Hipot Test (1 Minute)	2000 V
Hipot Test (2 Seconds)	2500 V
UL Insulation Class	H(180°C)
UL Temperature Code	1029B

Product Data	
Order product name	CORE & COIL HID 71A8241500DTA
EAN/UPC - Product	781087090459
Order code	913701119302
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	913701119302
Net Weight (Piece)	4.976 kg

## Dimensional drawing



HPS BAL 250W S50 480V/120T C&C

