



Core & Coil (71A) MH ~GT~ 450W

CORE & COIL HID MH BAL 750W M149 QUAD C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information			
ANSI Code	M149		
Lamp Type	750W MH		
Number of Lamps	1 piece/unit		
Circuit Type	SUPER-CWA		
Ballast Type	Magnetic HID		
Base Model	71A6492A		
Core Size	4 1/4 x 6 (2 Coil)		
Suitable For Outdoor Use	Yes		
Ignitor Catalog Number	LI573-H5		
Ignitor Temperature Rating	105°C		
Capacitor Value	28 MFD		
Capacitor Catalog Number	7C280S40		
Capacitor Requirements	400V		
Capacitor Temperature Rating	105°C		
Capacitor Diameter/Oval Dimensions 2 in			
Capacitor Height	4.8 in		
Automatic Restart	No		
Operating and Electrical			
Input Voltage	120/208/240/277 V		

Input Frequency	60 Hz
Inp. Current (Open Circuit)	3.07/1.52/1.54/1.37 A
Input Current (Starting)	6.15/3.53/3.06/2.66 A
Input Current (Short Circuit)	4.92-7.38/2.82-4.24/2.49-3.67/2.13-3.19 V
Secondary Short Circuit Current	4.9-6 A
Constant Wattage Deviation	10%
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Nominal Open Circuit Voltage	355 V
Input Current (Operating) (Nom)	6.95/3.9/3.5/3 A A
Input Power (Nom)	818 W
Rated Lamp Watts	750 W
Wiring	
Wire Striplength	0.5 mm
Wire Length by Color	12"
Wire Type	Stranded
Remote Wiring Configuration	Yes
Allowed	
Max Ballast-Lamp Distance Remote	3'
Wiring	


Datasheet, 2019, February 12 data subject to change

Core & Coil (71A) MH ~GT~ 450W

Recommended Fuse Value	20/10/10/8 A					
Approval and Application						
Open Circuit Voltage Test (Volts)	320-390 V					
Approbation Marks	ULR CSA certificate RoHS Compliant					
Temperature Marking	B/A/A/A					
UL Recognized	Yes					
Hipot Test (1 Minute)	2000 V					
Hipot Test (2 Seconds)	2500 V					
UL Insulation Class	H(180°C)					
UL Temperature Code	1029B					

Product Data	
Order product name	CORE & COIL HID MH BAL 750W M149 QUAD C&C
EAN/UPC - Product	781087122983
Order code	71A6492500DA
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	2
Material Nr. (12NC)	913701149502
Net Weight (Piece)	9.277 kg

Dimensional drawing



Product	C1	C2	A1	A2	А3	B1	B2
CORE & COIL HID 71A6492500DA	5 in	3 in	6 in	5.4 in	4.4 in	4.3 in	3.9 in

