



## Core & Coil (71A) HPS 200W - 400W

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

## **Product data**

General Information	
ANSI Code	S51-M169
Lamp type	400W HPS
Number of lamps	1 piece/unit
Circuit type	CWA
Ballast type	Magnetic HID
Base model	71A84Y3
Core size	4 x 4 (2 coil)
Suitable for outdoor use	Yes
Ignitor catalogue number	LI501-H4
Ignitor temperature rating	105°C
Capacitor value	55 MFD
Capacitor catalogue number	7C550P24RA
Capacitor requirements	240V
Capacitor temperature rating	105℃
Capacitor diameter/oval dimensions	1.80 in
Capacitor height	3.70 in
Automatic restart	No
Operating and Electrical	
Input voltage	230/400/480 V
Input frequency	60 Hz
Input current (open circuit)	0.95/0.55/0.46 A
Input current (starting)	1.8/1/0.85 A

Input current (short circuit)	1.44-2.16/0.81-1.21/0.68-1.02 A
Secondary short-circuit current	6.1-7.4 A
Constant wattage deviation	Within Trapezoid
Ballast factor (nom.)	1
Power factor (nom.)	0.90
Open circuit voltage	190 V
Input current (nom.)	2/1.2/1 A A
Input power (nom.)	465 W
Rated lamp power	400 W
Wiring	
Wire strip length	0.5 mm
Wire length by colour	12"
Wire type	Stranded
Remote wiring configuration allowed	Yes
Max. ballast-lamp distance remote	2'
wiring	
Recommended fuse value	5/3/3 A
Approval and Application	
Open circuit voltage test (volts)	170-210 V
Approval marks	ULR CSA certificate RoHS Compliant SASO
	Certificate
Temperature marking	D/C/D


Datasheet, 2019, March 22 data subject to change

## Core & Coil (71A) HPS 200W - 400W

UL recognised	Yes
Hipot test (1 minute)	2000 V
Hipot test (2 seconds)	2500 V
UL insulation class	H(180°C)
UL temperature code	1029D
Product Data	
Order product name	CORE & COIL HID HPS BAL 400W S51
	230/400/480V C&C

EAN/UPC – product	781087130322
Numerator – quantity per pack	1
Numerator – packs per outer box	3
Material no. (12NC)	913701151202
Net weight (piece)	7.154 kg

## Dimensional drawing



HPS BAL 400W S51 230/400/480V C&C

 Product
 C1
 C2
 A1
 A2
 B1
 B2

 CORE & COIL HID HPS BAL 400W S51
 4.20 in
 2.30 in
 4.8 in
 4.4 in
 4.3 in
 3.9 in

 230/400/480V C&C



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.