



Mark 10 Powerline

MARK 10 POWERLINE ELE DIMMING BALLAST (1) F24T5HO 120-277V

For companies looking to make their fixed-output linear T8, 4-pin CFL, and T5/HO fluorescent systems more cost effective and sustainable, Mark 10 Powerline ballasts provide an easy solution without the need for additional control leads. Simply, (1) replace the ballast, (2) replace the switch, (3) dim the lights, that is all it takes. It's that easy to bring the convenience and flexibility of fluorescent dimming to conference rooms, private offices, auditoriums, architectural cove lighting — anywhere dimming is required.

Product data

General Information			
Lamp Type	F24T5/HO		
Number of Lamps	1 piece/unit		
Ballast Type	Dimmable Fluorescent		
Base Model	IEZ124D		
Suitable For Outdoor Use	Yes		
Automatic Restart	Yes		
Operating and Electrical			
Input Voltage	120 to 277 V		
Input Frequency	50 to 60 Hz		
Max THD	10 %		
Starting Method	Programmed Start		
Lamp Current Crest Factor (Nom)	1.7		
Ignition Time (Nom)	1.5 s		
Ballast Factor (Max)	1.0		
Ballast Factor (Min)	0.03		
Power Factor (Nom)	0.99		
Input Current (Operating) (Max)	0.09 A		

Input Current (Operating) (Min)	0.21 A
Input Power (Max)	25 W
Input Power (Min)	8 W
Rated Lamp Watts	42 W
Wiring	
Color Input Terminals	BLK & WHT
Color Output Terminals	RED, YEL & BLU
Wire Striplength	0.375 mm
Control Wire Gauge	NA
Lamp Connection	Series
Wire Length by Color	No wires
Wire Gauge (Nom)	18AWG mm
Wire Type	Solid
Remote Wiring Configuration Allowed	No
Tandem Wiring Configuration Allowed	No
Through Wiring Configuration Allowed	No
Max Ballast-Lamp Distance Remote Wiring	No Remote
Max Ballast-Lamp Distance Tandem Wiring	NA

O 21 A

Innut Current (Operating) (Min)


Datasheet, 2019, February 12 data subject to change

Mark 10 Powerline

Max Ballast-Lamp Distance Through Wiring NA			
Connector Type	Poke-In		
Temperature			
T-Case Maximum (Nom)	70 °C		
Mechanical and Housing			
Housing Material	Metal		
Housing	D		
Housing Dimensions	16.7" x 1.18" x 1.0"		
Approval and Application			
EMC Immunity Standard	FCC Consumer		
Approbation Marks	UL certificate CEC Listing RoHS Compliant		
	CSA certificate		

Sound Rating	A		
UL Recognized	No		
Product Data			
Order product name	MARK 10 POWERLINE ELE DIMMING		
	BALLAST (1) F24T5HO 120-277V		
EAN/UPC - Product	781087132081		
Order code	IEZ124D35M		
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	12		
Material Nr. (12NC)	913701253802		
Net Weight (Piece)	441.000 g		

Dimensional drawing



ELE DIMMING BALLAST (1) F24T5HO 120-277V

Product	A1	B1	C1
MARK 10 POWERLINE IEZ124D35M	16.7 in	1.18 in	1.0 in

