



EB-T Electronic ballasts for TL-D lamps (India)

EBT 136 TLD

Compact, lightweight, high-frequency electronic standard ballasts for TL-D 36 W/ TL40 lamps

Product data


| Operating and Electrical | | | |
|--------------------------------|--|--|--|
| Input Voltage | 220 to 240 V | | |
| Line Frequency | 50 to 60 Hz | | |
| Input Frequency | 50 to 60 Hz | | |
| | | | |
| Wiring | | | |
| Connector Type Input Terminals | WAGO 251 universal connector [Suitable for both | | |
| | automatic wiring (ALF and ADS) and manual wiring] | | |
| Connector Type Output Terminal | s WAGO 251 universal connector [Suitable for both | | |
| | automatic wiring (ALF and ADS) and manual wiring] | | |
| | | | |
| Temperature | | | |
| Ambient temperature range | 0 °C to 50 °C | | |
| T-Case Maximum (Max) | 75 ℃ | | |
| | | | |
| Approval and Application | | | |
| Energy Efficiency Index | A3 | | |
| | | | |

| Safety Standard | IEC 61347-2-3 | |
|---------------------------------|-------------------|--|
| Approval Marks | CE marking S Mark | |
| | | |
| Product Data | | |
| Order product name | EBT 136 TLD | |
| Full product name | EBT 136 TLD | |
| Full product code | 871150099639800 | |
| Order code | 913702244812 | |
| Material Nr. (12NC) | 913702244812 | |
| Numerator - Quantity Per Pack | 1 | |
| EAN/UPC - Product/Case | 8711500996398 | |
| Numerator - Packs per outer box | 6 | |
| EAN/UPC - Case | 8727900078398 | |
| | | |

Datasheet, 2023, September 4 data subject to change

EB-T Electronic ballasts for TL-D lamps (India)

Dimensional drawing



| Product | D1 | C1 | A1 | A2 | B1 |
|-------------|--------|---------|----------|----------|---------|
| EBT 136 TLD | 4.0 mm | 30.0 mm | 210.0 mm | 200.0 mm | 40.0 mm |

