



# Electronic parallel ignitor for HID lamp circuits

## SI 51 Plus

HID ignitors for parallel systems

#### **Product data**

Operating and Electrical				
Input Voltage	220 to 240 V	220 to 240 V		
Line Frequency	50 to 60 Hz			
Input Frequency	50 to 60 Hz			
Wiring				
Connector Type	Screw			
Temperature				
Ambient temperature range	-20 °C to 75 °C			
T-Case Maximum (Max)	80 °C			
Mechanical and Housing				


Housing

Akulon S223

Approval and Application	
Approval Marks	CE marking ENEC certificate
Product Data	
Order product name	SI 51 Plus
Full product name	SI 51 Plus
Full product code	871016305621030
Order code	05621030
Material Nr. (12NC)	913710011114
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8710163056210
Numerator - Packs per outer box	48
EAN/UPC - Case	8710163056227

## Electronic parallel ignitor for HID lamp circuits

### Dimensional drawing



Product	C1	A1	A2	B1	D1
SI 51 Plus	38.5 mm	85.5 mm	65.0 mm	41.5 mm	4.3 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, April 30 - data subject to change