



# Electronic parallel ignitor for HID lamp circuits

# SI 51 Plus

HID ignitors for parallel systems

### **Product data**

Operating and Electrical		
Input Voltage	220 to 240 V	
Line Frequency	50 to 60 Hz	
Input Frequency	50 to 60 Hz	
Wiring		
Connector Type	Screw	
Temperature		
Ambient temperature range	-20 °C to 75 °C	
T-Case Maximum (Max)	80 ℃	
Mechanical and Housing		
Housing	Akulon S223	

Approval and Application		
Approval Marks	CE marking ENEC certificate	
Product Data		
Order product name	SI 51 Plus	
Full product name	SI 51 Plus	
Full product code	871016305621030	
Order code	913710011114	
Material Nr. (12NC)	913710011114	
Numerator - Quantity Per Pack	1	
EAN/UPC - Product/Case	8710163056210	
Numerator - Packs per outer box	48	
EAN/UPC - Case	8710163056227	

Datasheet, 2023, October 26 data subject to change

# Electronic parallel ignitor for HID lamp circuits

## Dimensional drawing

Product	C1	A1	A2	B1	D1
SI 51 Plus	38.5 mm	85.5 mm	65.0 mm	41.5 mm	4.3 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.