



e-Vision Low Wattage 20-150W

E-VISION ELE MH BAL 150W M102/142 120-277V 50/60H

Low frequency electronic HID ballasts such as the Philips Advance e-Vision line constantly measure and adjust the wattage, optimizing delivery of the ceramic lamps' superior color properties. This makes ceramic metal halide operated by e-Vision ballasts the premier choice for many applications previously illuminated by either tungsten halogen or incandescent sources, such as retail lighting.

Product data

C102-M102,C142-M142				
150W MH				
1 piece/unit				
Electronic HID				
IMH150HLF				
Yes				
120 to 277 V				
50 to 60 Hz				
15 %				
1.8				
1200 s				
1				
0.90				
1.4 A				
0.6 A				

Input Power (Nom)	165-161 W
Rated Lamp Power	150 W
Wiring	
Color Input Terminals	No terminals
Color Output Terminals	No terminals
Wire Striplength	0.50 mm
Control Wire Gauge	NA
Wire Length by Color	All leads = 11"
Wire Gauge (Nom)	18AWG mm
Wire Type	Stranded
Remote Wiring Configuration Allowed	Yes
Tandem Wiring Configuration Allowed	No
Through Wiring Configuration Allowed	No
Connector Type	No connector


Datasheet, 2019, March 22 data subject to change

e-Vision Low Wattage 20-150W

Temperature						
T-Case Maximum (Nom)	85 ℃					
Mechanical and Housing						
Housing Material	Metal					
Housing	Н					
Housing Dimensions	5.7" x 3.6" x 1.5"					
Approval and Application						
EMC Immunity Standard	FCC Non-Consumer					
Approval Marks	CSA certificate UL certificate NOM certificate					
	RoHS Compliant					
Hum And Noise Level	A					

UL Recognized	No
Product Data	
Order product name	E-VISION ELE MH BAL 150W M102/142 120-277V
	50/60H
EAN/UPC - Product	781087055595
Order code	913710295902
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	913710295902
Net Weight (Piece)	0.885 kg

Dimensional drawing



E-VISION IMH150HLFM

Product	A1	A2	А3	A4	B1	B2	C1
E-VISION ELE MH BAL 150W	6.3 in	5.7 in	6.0 in	2.0 in	3.6 in	2.9 in	1.5 in
M102/142 120-277V 50/60H							

