



Core & Coil (71A) HPS 200W - 400W

CORE & COIL HID HPS BAL 250W S50 480V C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information		
ANSI Code	S50	
Lamp Type	250W HPS	
Number of Lamps	1 piece/unit	
Circuit Type	CWA	
Ballast Type	Magnetic HID	
Base Model	71A8241	
Core Size	4 x 4 (2 coil)	
Suitable For Outdoor Use	Yes	
Ignitor Catalog Number	LI501-H4	
Ignitor Temperature Rating	105°C	
Capacitor Value	35 MFD	
Capacitor Catalog Number	7C350P24RA	
Capacitor Requirements	240V	
Capacitor Temperature Rating	105°C	
Capacitor Diameter/Oval Dimensions	1.65 in	
Capacitor Height	3.7 in	
Automatic Restart	No	
Operating and Electrical		
Input Voltage	480 V	

Input Frequency	60 Hz
Input Current (Open Circuit)	0.45 A
Input Current (Starting)	0.4 A
Input Current (Short Circuit)	0.25-0.45 A
Secondary Short Circuit Current	3.7-4.5 A
Constant Wattage Deviation	Within Trapezoid
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Open Circuit Voltage	187 V
Input Current (Nom)	0.63 A A
Input Power (Nom)	310 W
Rated Lamp Power	250 W
Wiring	
Wire Striplength	0.5 mm
Wire Length by Color	12"
Wire Type	Stranded
Remote Wiring Configuration Allowed	Yes
Max Ballast-Lamp Distance Remote Wiring	: 2'
Recommended Fuse Value	2 A


Datasheet, 2019, February 12 data subject to change

Core & Coil (71A) HPS 200W - 400W

Approval and Application	
Open Circuit Voltage Test (Volts)	170-205 V
Approval Marks	ULR CSA certificate RoHS Compliant
Temperature Marking	В
UL Recognized	Yes
Hipot Test (1 Minute)	2000 V
Hipot Test (2 Seconds)	2500 V
UL Insulation Class	H(180°C)
UL Temperature Code	1029B
Product Data	
Order product name	CORE & COIL HID HPS BAL 250W S50 480V
	C&C

EAN/UPC - Product	781087032923
Order code	490391
Local order code	490391
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	3
Material Nr. (12NC)	913710471502
Net Weight (Piece)	5.103 kg

Dimensional drawing



Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 71A8241510D	3.45 in	1.8 in	4.8 in	4.4 in	4.3 in	3.9 in

