



Core & Coil (71A) MH ~LT~ 175W

CORE & COIL HID MH BAL 150W M102/142 480V/120T C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information					
ANSI Code	M102-M142				
Lamp Type	150 MH				
Number of Lamps	1 piece/unit				
Circuit Type	HX-HPF				
Ballast Type	Magnetic HID				
Base Model	71A5442T				
Core Size	3 X 4 (2 coil)				
Suitable For Outdoor Use	Yes				
Ignitor Catalog Number	LI533-H4				
Ignitor Temperature Rating	105°C				
Capacitor Value	16 MFD				
Capacitor Catalog Number	7C160M30RA				
Capacitor Requirements	280V				
Capacitor Temperature Rating	105°C				
Capacitor Diameter/Oval Dimensions	1.65 in				
Capacitor Height	2.75 in				
Automatic Restart	No				

Operating and Electrical	
Input Voltage	480 V
Input Frequency	60 Hz
Input Current (Open Circuit)	0.81 A
Input Current (Starting)	0.45 A
Input Current (Short Circuit)	0.33-0.49 A
Secondary Short Circuit Current	1.91-2.33 A
Constant Wattage Deviation	10%
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Open Circuit Voltage	270 V
Input Current (Nom)	0.42 A A
Input Power (Nom)	185 W
Rated Lamp Power	150 W
Wiring	
Wire Striplength	0.5 mm
Wire Length by Color	12"
Wire Type	Stranded
Remote Wiring Configuration Allowed	Yes


Datasheet, 2019, March 22 data subject to change

Core & Coil (71A) MH ~LT~ 175W

Max Ballast-Lamp Distance Remote Wiring 10'					
Recommended Fuse Value	3 A				
Approval and Application					
Open Circuit Voltage Test (Volts)	243-297 V				
Approval Marks	ULR CSA certificate RoHS Compliant				
Temperature Marking	В				
UL Recognized	Yes				
Hipot Test (1 Minute)	2000 V				
Hipot Test (2 Seconds)	2500 V				
UL Insulation Class	H(180°C)				
UL Temperature Code	1029B				

CORE & COIL HID MH BAL 150W M102/142
480V/120T C&C
781087026335
482612
482612
1
4
913710491402
4.078 kg

Dimensional drawing



MH BAL 150W M102/142 480V/120T C&C

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID MH BAL 150W	3.92 in	2.8 in	3.9 in	3.5 in	2.8 in	2.4 in
M102/142 480V/120T C&C						

