



## Core & Coil (71A) MH 175W - 450W

# CORE & COIL HID MH BAL 320W M132/M154 QUAD C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

#### **Product data**

| General Information                |                        |
|------------------------------------|------------------------|
| ANSI Code                          | M132-M154              |
| Lamp Type                          | 320W MH                |
| Number of Lamps                    | 1 piece/unit           |
| Circuit Type                       | SUPER-CWA              |
| Ballast Type                       | Magnetic HID           |
| Base Model                         | 71A5892A               |
| Core Size                          | 4 1/4 x 4 3/4 (2 coil) |
| Suitable For Outdoor Use           | Yes                    |
| Ignitor Catalog Number             | LI533-H4               |
| Ignitor Temperature Rating         | 105°C                  |
| Capacitor Value                    | 21 MFD                 |
| Capacitor Catalog Number           | 7C210P40R              |
| Capacitor Requirements             | 400V                   |
| Capacitor Temperature Rating       | 105°C                  |
| Capacitor Diameter/Oval Dimensions | 1.75 in                |
| Capacitor Height                   | 4.80 in                |
| Automatic Restart                  | No                     |
|                                    |                        |

| Operating and Electrical            |                                   |
|-------------------------------------|-----------------------------------|
| Input Voltage                       | 120/208/240/277 V                 |
| Input Frequency                     | 60 Hz                             |
| Inp. Current (Open Circuit)         | 2.3/1.35/1.15/1 A                 |
| Input Current (Starting)            | 2.1/1.2/1.05/0.95 A               |
| Input Current (Short Circuit)       | 1.65-2.5/1-1.5/0.8-1.25/0.7-1.1 A |
| Secondary Short Circuit Current     | 2.9-3.6 A                         |
| Constant Wattage Deviation          | 10%                               |
| Ballast Factor (Nom)                | 1                                 |
| Power Factor (Nom)                  | 0.90                              |
| Nominal Open Circuit Voltage        | 270 V                             |
| Input Current (Operating) (Nom)     | 3.25/1.9/1.65/1.4 A A             |
| Input Power (Nom)                   | 368 W                             |
| Rated Lamp Watts                    | 320 W                             |
|                                     |                                   |
| Wiring                              |                                   |
| Wire Striplength                    | 0.5 mm                            |
| Wire Length by Color                | 12"                               |
| Wire Type                           | Stranded                          |
| Remote Wiring Configuration Allowed | Yes                               |


Datasheet, 2019, March 22 data subject to change

### Core & Coil (71A) MH 175W - 450W

| Max Ballast-Lamp Distance Remote  | 2'                                       |
|-----------------------------------|--|
| Wiring                            |  |
| Recommended Fuse Value            | 8/6/5/3 A                                |
|                                   |  |
| Approval and Application          |  |
| Open Circuit Voltage Test (Volts) | 250-300 V                                |
| Approbation Marks                 | ULR CSA certificate NOM certificate RoHS |
|                                   | Compliant                                |
| Temperature Marking               | B/B/B/B                                  |
| UL Recognized                     | Yes                                      |
| Hipot Test (1 Minute)             | 2000 V                                   |
| Hipot Test (2 Seconds)            | 2500 V                                   |
| UL Insulation Class               | H(180°C)                                 |

| UL Temperature Code             | 1029B                                 |
|---------------------------------|---------------------------------------|
|                                 |                                       |
| Product Data                    |                                       |
| Order product name              | CORE & COIL HID MH BAL 320W M132/M154 |
|                                 | QUAD C&C                              |
| EAN/UPC - Product               | 781087054659                          |
| Order code                      | 71A5892500DMLA                        |
| Numerator - Quantity Per Pack   | 1                                     |
| Numerator - Packs per outer box | 2                                     |
| Material Nr. (12NC)             | 913710501809                          |
| Net Weight (Piece)              | 5.249 kg                              |
|                                 |                                       |

#### Dimensional drawing



MH BAL 320W M132/M154 QUAD C&C

 Product
 C1
 C2
 A1
 A2
 B1
 B2

 CORE & COIL HID MH BAL 320W M132/
 3.65 in
 1.8 in
 4.8 in
 4.4 in
 4.3 in
 3.9 in

 M154 QUAD C&C

