



F-can (72C)

F-CAN HID MH BAL 150W M102/142 120/277 FCAN

The Philips Advance line of F-can HID ballasts comes in two dual-voltage configurations for the US and Canadian market. Ballasts for these luminaires are most often encased and potted in fluorescent ballast type cans.

Product data

General Information	
ANSI Code	M102-M142(PULSESTART)
Lamp Type	150W MH
Number of Lamps	1 piece/unit
Circuit Type	HX-HPF
Ballast Type	Magnetic HID
Base Model	72C5482NP900
Suitable For Outdoor Use	Yes
Ignitor Catalog Number	Inside Can
Capacitor Catalog Number	Inside Can
Automatic Restart	No
Operating and Electrical	
Input Voltage	120/277 V
Input Frequency	60 Hz
Input Current (Open Circuit)	3.65/1.55 A
Input Current (Starting)	1.5/0.75 A
Input Current (Short Circuit)	1.45-2.15/0.6-0.95 A
Secondary Short Circuit Current	2.0-2.5 A
Constant Wattage Deviation	12%
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Open Circuit Voltage	277 V
Input Current (Nom)	1.6/0.7 A A

Input Power (Nom)	180 W	
Rated Lamp Power	150 W	
Wiring		
Wire Striplength	0.5 mm	
Wire Length by Color	12"	
Wire Type	Stranded	
Remote Wiring Configuration Allowed	Yes	
Max Ballast-Lamp Distance Remote Wiring 50'		
Recommended Fuse Value	10/4 A	
Mechanical and Housing		
Housing Material	Metal	
Housing	F-Can	
Housing Dimensions	14.3 x 2.63 x 3.19	
Approval and Application		
Open Circuit Voltage Test (Volts)	250-300 V	
Approval Marks	CSA certificate UL certificate RoHS	
	Compliant	
Temperature Marking	90°C max. case	
UL Recognized	No	
Hipot Test (1 Minute)	1600 V	
Hipot Test (2 Seconds)	2000 V	


Datasheet, 2019, February 12 data subject to change

F-can (72C)

UL Insulation Class	A(105°C)
UL Temperature Code	NA
Product Data	
Order product name	F-CAN HID MH BAL 150W M102/142
	120/277 FCAN
EAN/UPC - Product	781087029930
Order code	494229

Local order code	494229
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	2
Material Nr. (12NC)	913710564002
Net Weight (Piece)	5.657 kg

Dimensional drawing



MH BAL 150W M102/142 120/277 FCAN

