PHILIPS Lighting



Core & Coil (71A) MH ~GT~ 450W

CORE & COIL HID MH BAL 1000W M47 347/480/120T C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

| General Information | | |
|------------------------------------|------------------------|--|
| ANSI Code | M47 | |
| Lamp Type | 1000W MH | |
| Number of Lamps | 1 piece/unit | |
| Circuit Type | CWA | |
| Ballast Type | Magnetic HID | |
| Base Model | 71A65F0T | |
| Core Size | 4 1/4 x 4 3/4 (2 coil) | |
| Suitable For Outdoor Use | Yes | |
| Ignitor Catalog Number | NA | |
| Ignitor Temperature Rating | NA | |
| Capacitor Value | 24 MFD | |
| Capacitor Catalog Number | MD2409000 | |
| Capacitor Requirements | 480V | |
| Capacitor Temperature Rating | 90°C | |
| Capacitor Diameter/Oval Dimensions | 1.75 in | |
| Capacitor Height | 3.9 in | |
| Automatic Restart | No | |


| Operating and Electrical | |
|-------------------------------------|---------------------|
| Operating and Electrical | |
| Input Voltage | 347/480/120T V |
| Input Frequency | 60 Hz |
| Inp. Current (Open Circuit) | 1.5/1.1 A |
| Input Current (Starting) | 2.5/1.8 A |
| Input Current (Short Circuit) | 1.95-2.95/1.4-2.1 V |
| Secondary Short Circuit Current | 4.9-6.1 A |
| Constant Wattage Deviation | 10% |
| Ballast Factor (Nom) | 1 |
| Power Factor (Nom) | 0.90 |
| Nominal Open Circuit Voltage | 415 V |
| Input Current (Operating) (Nom) | 3.1/2.25 A A |
| Input Power (Nom) | 1070 W |
| Rated Lamp Watts | 1000 W |
| | |
| Wiring | |
| Wire Striplength | 0.5 mm |
| Wire Length by Color | 12" |
| Wire Type | Stranded |
| Remote Wiring Configuration Allowed | Yes |
| | |

Core & Coil (71A) MH ~GT~ 450W


| Max Ballast-Lamp Distance Remote Wiring Determined by AWG used | |
|--|------------------------------------|
| Recommended Fuse Value | 8/6 A |
| | |
| Approval and Application | |
| Open Circuit Voltage Test (Volts) | 370-460 V |
| Approbation Marks | ULR CSA certificate RoHS Compliant |
| Temperature Marking | D/D |
| UL Recognized | Yes |
| Hipot Test (1 Minute) | 2000 V |
| Hipot Test (2 Seconds) | 2500 V |
| UL Insulation Class | H(180°C) |
| UL Temperature Code | 1029D |

| Product Data | |
|---------------------------------|----------------------------------|
| Order product name | CORE & COIL HID MH BAL 1000W M47 |
| | 347/480/120T C&C |
| EAN/UPC - Product | 781087042014 |
| Order code | 71A65F0600T |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 2 |
| Material Nr. (12NC) | 913710575002 |
| Net Weight (Piece) | 8.608 kg |
| | |

Dimensional drawing



MH BAL 1000W M47 347/480/120T C&C





© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2019, February 12 - data subject to change